

A vertical photograph of a forest. The scene is misty and ethereal. In the foreground, several dark, slender tree trunks stand prominently, some with small, bright green leaves. The background is a dense forest of similar trees, their forms softened by a light mist or fog. The overall color palette is muted, with greys, greens, and soft whites.

Bullerjan®

Bullerjan dot®.



Bullerjan® dot model 2017

Developing stoves which are special in their design, form and function, has always been a fundamental principle of Bullerjan.

Its clear-cut and modern design and look makes the dot® stand out – however, what really sets this stove apart is the beauty of its flames.

The deep, rounded and brightly lined fire chamber creates a very beautiful firebox, which enables exceptionally stable and balanced burning. The large and high window of the dot® offers a perfect view of the easily regulated interplay of flames with its inimitable shine.

In regard to environmental and technical standards, the dot® exceeds all current requirements – its quality finishing makes it robust and durable.

- 6 kW nominal heat output at 80 % efficiency
- Individual design options with the KLASSIK and DESIGN equipment sets
- Adjustable air intake for exact control over the flame image
- Well functioning screen rinsing
- Self-closing and -locking door
- Firebox lining out of high-grade Thermotte
- Easy to clean because of ash grate and ash holder
- Possibility to connect an external combustion air supply
- Flue connection either on the top or at the rear
- Height adjusters integrated in the pedestal
- Approved for use with firewood and brown coal briquettes





Product features – technical details

Bullerjan® dot model 2017

For full information and advice please contact your authorized Bullerjan dealer or our customer service by telephone.

Dimensions

Depth	69.5 cm
Width	66.6 cm
Height	102 cm
Weight	187 kg
Depth of combustion chamber	37.4 cm
Exhaust gas nozzle	Ø 15 cm
Height centre exhaust gas nozzle rear	ca. 85.3 cm
Air supply nozzle	Ø ca. 10 cm
Height centre air supply nozzle	ca. 33 cm
Distance from combustible materials (front/back/sides/floor)	95/45/30/0 cm

high cube

Depth	69.5 cm
Width	66.6 cm
Height	102 cm
Weight	187 kg
Depth of combustion chamber	37.4 cm
Exhaust gas nozzle	Ø 15 cm
Height centre exhaust gas nozzle rear	ca. 85.3 cm
Air supply nozzle	Ø ca. 10 cm
Height centre air supply nozzle	ca. 33 cm
Distance from combustible materials (front/back/sides/floor)	95/45/30/0 cm

Performance

Nominal heat capacity (NWL)	6.0 kW
Exhaust gas mass flow rate at NWL	7.5 g/s
Delivery pressure	0.12 mbar
Mean exhaust gas temperature	230 °C
CO-content (13 % O ₂)	1229 mg/m ³
Dust (13 % O ₂)	28 mg/m ³
Efficiency	80 %
EEL	106
Energy efficiency class	A



Bullerjan dot model 2017
Cover: KLASSIK
Flue connection at the rear



Bullerjan dot model 2017
Cover: DESIGN
Flue connection at the rear

Product registration / extended warranty

Please register your Bullerjan dot online and extend thereby the warranty to 5 years (cg. warranty terms on www.bullerjan.com).

Errors and modifications reserved.

Art Direction: Antonia Henschel, Sign Kommunikation GmbH, www.sign.de
Cover Photography: Max Ratjen

Printed on Munken Pure
FSC™ – The mark of responsible forestry. www.fsc.org.
Printed in Germany

Version: 01/2018



Bullerjan dot model 2017
Cover: KLASSIK
Flue connection on the top



Bullerjan dot model 2017
Cover: DESIGN
Flue connection on the top



Bullerjan®

Bullerjan GmbH
Neuwarmbüchener Straße 2
D-30916 Isernhagen
Tel +49(0)5136/9775-0
Fax +49(0)5136/9775-10
info@bullerjan.com
www.bullerjan.com

www.bullerjan.com