

## **PR-RMP Introduction**

## PN# PR-RMP




Macnaught USA's MX Series of Flow Meters offers our <u>Remote</u> Mount PR-RMP Display option. This display provides Rate, re-settable Batch and Totalizer and non re-settable Totalizer. Battery powered with up to 3 year battery life.



Construction	PR-RMP
Material	Display Housing: Polypropylene Wall Mount Plate: Aluminium
IP rating	IP67
Mounting	Wall Mount
Cable Entry	(2) x M12 * 1.5 1 x cable gland included

LC Display	PR-RMP
Digit Size	Upper LCD 7 Digits (12 mm) Lower LCD 7 Digits (8 mm)
Display	Flow Rate (Various units) Totalizer (Resettable) Batch Totalizer (Resettable) Accumulated Totalizer (Non-Resettable)

Technical Specifications	PR-RMP
Signal inputs	Reed Switch (can be used with battery)
Signal outputs	None
Power supply	Battery: 3.6 V Lithium External: not available
Temperature	-20°C to 80°C -4°F to 176°F
Backup	EEPROM (Flash memory)
Backlight	No
Ex Approvals	No





Macnaught USA Inc. 614 S Ware Blvd Tampa FL 33619 **Ph: (813) 613-8877 Email:** info@macnaughtusa.com **Website:** macnaughtusa.com