OIL CONTROL GUNS - METERED

Control guns - metered (HG series)

Top of the range pre-settable electronic oil control gun with rigid extension. Features include, locking trigger and non-drip nozzle, 5 pre-settable totals, resettable batch total and a non-resttable total. The meter accuracy is +/-0.5% of reading, working pressures up to 1500psi (10,350kPa) and flow rates from 1 to 30LPM (4 to 8 US gal/min) the gun features a self correcting function for viscosity change.



Automatic non drip nozzle

Self correcting algorithm for accuracy

Positive latch release mechanism

5 pre-settable totals

Heavy duty construction

Rotating ball

bearing swivel

Features & Benefits

- HG-SERIES oil gun with pre-set digital display
- For oils up to SAE140 viscosity with +/-0.5% accuracy
- Maximum working pressure 10,350 kPa (1500 psi) through either of two outlets (dual outlet)
- Flow rate up to 30L(8gal)/min
- Rigid extension with non-drip automatic nozzle

Value Proposition

Easy to operate accurate pre-settable gun with 5 storable presets. Accurate control and measurement of oil usage.

Technical Specifications

- Accuracy: + 0.5% (of Reading) (ISO100 @ 10 I/min)
- Flow Range: 1-30 l/min (0.26 8 US gal/min)
- Maximum Pressure: 103.50 BAR / 10350kPa / 1500 PSI
- Weight: 1.16kg (2.55lbs)
- Swivel Inlet: 1/2" NPT
- Outlet: 3/8" NPT
- Operating Temperature: -0 to +50 degrees Celsius (32 122 degrees F)
- Battery: 2 x 1.5Volt AA Batteries (Alkaline batteries are essential for HG60 version)
- Fluid Compatibility: Engine Oil, Diesel Oil, Automatic Transmission Fluid, Anti-freeze / Anti-Boil Mixture. (Maximum Viscosity SAE140)
- Dimensions: 25.8cm (10inch) Long x 9.5 cm (3.7inch)
 High, 11cm(4.33inch) wide (Dimensions without extension)

Package Includes:

• Gun complete with rigid extension and automatic nozzle

Recommended Additional Offerings:

- T512-02 5:1 Ratio oil pump
- OMP310B-02 Retracta oil reel (1/2"x15m)

Applications:

Automotive, Truck and Buses, Farming, Construction and Earthmoving, Military, Mining, Aircraft, Trains





	HG40R-02 Mechanical	HG55-02 Electronic	HG60R-02 Electronic Preset
Flow range	1-30L(0.26-8gal)/min	1-30L(0.26-8gal)/min	1-30L(0.26-8gal)/min
Inlet swivel	1/2" NPT (F)	1/2" NPT (F)	1/2" NPT (F)
Meter	oval gear / mechanical	oval gear / digital	oval gear / digital
Meter accuracy (Flow rate)	+/- 1% (lube oils)	+/-0.5% (lube oils)	+/- 0.5% (lube oils)
Features	4-digit resettable batch totaliser 6-digit accumulative totaliser	5-digit resettable batch totaliser 6-digit accumulative totaliser sleep mode to conserve battery life EEPROM information retention for battery change	pre-settable to 1999.9ltrs, AUTO Shutoff 5-digit resettable batch totaliser 6-digit accumulative totaliser sleep mode to conserve battery life EEPROM information retention for battery change
Extension	rigid	rigid	rigid
Non drip nozzle	automatic	automatic	automatic
Latching trigger	✓	✓	✓
Fully serviceable	✓	✓	✓

Note¹ Subject to Macnaught warranty terms and conditions, see inside back cover. Note² Parts available for 10 years from deletion or upgrade of model. **BSP models available**

Oil control gun accessories



AUTOMATIC NOZZLE HGNZL Fully automatic non-drip nozzle





RIGID EXTENSION HGREX 150 mm (6") rigid extension



FLEXIBLE EXTENSION HGFNZ 250mm (10") flexi

HGFNZ
250mm (10") flexible
extension with non drip nozzle



FLEXIBLE EXTENSION HGFEX

extension

250 mm (10") flexible

