

# P3 POWERLUBE®

## AIR OPERATED GREASING SYSTEM (P3-01C)

**10 Year Warranty**

\*conditions apply

### PRODUCT OVERVIEW

The P3 POWERLUBE™ is a premium quality, reliable, 50:1 air-operated greasing system that is excellent for high volume grease users that have many applications and require continuous high pressure greasing.

This portable grease dispensing system is suitable for 20kg pails and is equipped with a low air consumption motor that doesn't need to be lubricated due to the use of modern polymer materials.

Users will save on power and the oily mist and mess associated with air operated equipment is gone.

Suitable for underground coal mine applications.

### FEATURES & BENEFITS

**50:1 Ratio Air Motor**  
Delivers up to 460g/min for fast, efficient greasing. Instant delivery of up to 50 times applied air pressure

**B2 Booster Gun**  
Boosts pressure up to 10,000psi to clear blocked grease nipples

**KY Supergrip Coupler**  
Positive no-leak connection ensures grease reaches the bearing

**360° ZSB Swivel**  
Improves manoeuvrability and offers easier one-handed operation

**Fully Repairable**  
Provides a much longer service life

**Quiet Air Motor Design**  
Meets all industry noise level standards. Doesn't require air-line lubricator. Zinc components suitable for underground mining applications.

**Adjustable Collar System**  
To accommodate different height 20kg (or similar size) grease pails

**Rubber-Edged Follower Plate**  
Wipes container clean & prevents air pockets & contamination

**Fully Sealed With Grease Strainer**  
Delivers clean contamination free grease to the application

**4m High Pressure Grease Hose**  
Allows access to hard to reach applications



### TECHNICAL SPECIFICATIONS

P3001 (50:1) Air-operated pump
4m x 6mm ID delivery hose
Compatible with 20kg (or similar size) pails
Grease viscosity up to NLGI No.2
Output 460g/min (at pump)
Maximum pump output pressure: 51,700kPa (7,500psi)
Maximum gun output pressure: 68,900kPa (10,000psi)
Maximum air pressure: 150psi
Minimum air pressure: 60psi
Pump inlet/outlet: 1/4" NPT (F)
Minimum compressor size: 0.08m³/min (3cfm)

### OPTIONAL ACCESSORIES

### PACKAGE INCLUDES

P3001 pump unit
Lid & rubber edged follower plate
4m high pressure hose
B2 booster gun
KY Supergrip coupler
ZSB high pressure swivel
Instruction manual

**For more information visit [www.macnaught.com.au/p3-01c](http://www.macnaught.com.au/p3-01c)**

**MACNAUGHT Pty Ltd**  
41-49 Henderson Street  
Turrella, NSW, 2205  
Australia

**T** +61 2 9567 0401  
**F** +61 2 9597 7773  
**E** [info@macnaught.com.au](mailto:info@macnaught.com.au)  
**W** [www.macnaught.com.au](http://www.macnaught.com.au)

**MACNAUGHT USA Inc**  
614 South Ware Boulevard  
Tampa, Florida, 33619  
United States

**T** +1813 628 5506  
**F** +1509 694 8495  
**E** [info@macnaughtusa.com](mailto:info@macnaughtusa.com)  
**W** [www.macnaughtusa.com](http://www.macnaughtusa.com)