

Specifications – Standard Unit Without Options

Size:	7.3 in. wide x 8.3 in. high x 3.4 in. deep
Shipping weight:	6 lb including shipping container
Power supply:	One lithium battery (supplied with instrument), Part No. 100005111 Average battery life: 3 to 5 years
Temperature range:	-40 to +140°F (-40 to +60°C)
Totalizer:	Six digits, 0.5 in. character height, registering barrels (1/10, 1/100 available)* Divisor or calibration factor range: 0.001 to 999,999
Flow rate:	Six digits, registering barrels per day* Updates once per second
Accuracy:	±1 count (totalizer)
Input frequency:	0 to 3500 Hz
Input amplitude:	30 to 3000 mV peak to peak
Signal cable:	1-ft length
Mounting:	MC-II enclosure mounts directly on a weatherproof pickup adapter (provided) which threads onto the turbine meter. The pickup adapter tilts and swivels for ease in optimizing visibility of the displays.
Compliances:	CSA certified intrinsically safe in hazardous locations Class I, Division 1, Groups A,B,C,D Type 4 enclosure

Distributed by:



**DIAMOND
SCIENTIFIC**

625 Peachtree Street
Cocoa, FL 32922
Phone: 1-321-223-7500

info@diamondsci.com
www.DiamondSci.com



* Default settings are barrels (volume) and barrels per day (rate) unless otherwise specified at the time of order.