



# ALFLAG PN16 Adapter Flange

- Model | ALFLAG
- Size | 2" thru 12"
- Approvals | UL, ULC, FM

- Housing | Ductile Iron ASTM A536 Gr. 65-45-12
- Working Pressure | 250 PSI / 1.60 Mpa
- Paint Color | Orange Enamel, Optional : Red



PN stands for Nominal Pressure and roughly equates to the number of bar. (i.e. the cold working pressure of PN16 is 16 bar = 232 psi)

## Adaptor Flange

Nominal Size		Pipe OD.		Dimensions								Mating Bolt Dia.	
in	mm	in	mm	L		Flange O.D (X)		Bolt Circle (Y)		Bolt Hole (Z)		No.	mm
				in	mm	in	mm	in	mm	in	mm		
2	50	2.375	60.3	1.97	50	6.02	165	4.92	125	0.51	13	4	M16
2½	65	2.875	73	1.97	50	6.89	185	5.71	145	0.51	13	4	M16
2½	65	3	76.1	1.97	50	6.89	185	5.71	145	0.51	13	4	M16
3	80	3.5	88.9	2.36	60	7.48	200	6.3	160	0.51	13	8	M16
4	100	4.25	108	2.76	70	8.27	220	7.09	180	0.71	18	8	M16
4	100	4.5	114.3	2.76	70	8.58	220	7.09	180	0.71	18	8	M16
5	125	5.25	133	2.76	70	8.58	250	7.09	210	0.71	18	8	M16
5	125	5.5	139.7	2.76	70	8.58	250	7.09	210	0.71	18	8	M16
5	125	5.563	141.3	2.76	70	8.58	250	7.09	210	0.71	18	8	M20
6	150	6.25	159	2.76	70	11.1	285	9.44	240	0.71	18	8	M20
6	150	6.5	165.1	2.76	70	11.1	285	9.44	240	0.71	18	8	M20
6	150	6.625	168.3	2.76	70	11.1	285	9.44	240	0.71	18	8	M20
8	200	8.625	219.1	3.15	80	13.11	340	11.61	295	0.75	19	12	M20
10	250	10.75	273	3.54	90	15.63	405	13.98	355	0.79	20	12	M24
12	300	12.75	323.9	3.94	100	18.11	460	16.14	410	0.91	23	12	M24