



ALRCG Grooved Reducing Cross



- Model | ALRCG
- Size | 4" x 2" thru 6" x 4"
- Approvals | UL, ULC, FM
- Housing | Ductile Iron ASTM A536 Gr. 65-45-12
- Working Pressure
 - UL, ULC, FM | 300 PSI / 2.07 Mpa
 - Mechanical | 500 PSI / 3.45 Mpa
- Paint Color | Orange Enamel, Optional : Red



Grooved Reducing Cross

Nominal Size		Pipe OD.		Dimensions	
in	mm	in	mm	L	
				in	mm
4 x 2	100 x 50	4.500 x 2.375	114.3 x 60.3	5	127
4 x 1/2	100 x 65	4.500 x 3.000	114.3 x 76.1	5	127
4 x 3	100 x 80	4.500 x 3.500	114.3 x 88.9	5	127
6 x 4	150 x 100	6.500 x 4.500	165.1 x 114.3	6.5	165
6 x 2	150 x 50	6.625 x 2.375	165.3 x 60.3	6.5	165
6 x 2 1/2	150 x 65	6.625 x 3.000	165.3 x 76.1	6.5	165
6 x 3	150 x 80	6.625 x 3.500	165.3 x 88.9	6.5	165
6 x 4	150 x 100	6.625 x 4.500	165.3 x 114.3	6.5	165