

Slip Resist

Additive

TECHNICAL DATA SHEET



Anti-Slip Grit Additive

Description

RainguardPro® Slip Resist is a durable, aluminum oxide aggregate developed for use as an anti-skid additive for interior and exterior paint, epoxy and sealers. It adds a slight texture to the finish without changing colors. It has excellent resistance to chemicals and detergents.

Uses

Slip Resist can be used in water-based, solvent based alkyd, urethane or epoxy coatings and is not recommended for repellents, silicones or wax-based coatings.

Safety

Use with adequate ventilation. Wear appropriate, properly fitted dust mask and avoid breathing dust and particles. Wear appropriate skin, eye protection. In case of eye contact, flush immediately with water. If irritation persists, consult a Physician. Wash hands with soap & water after use and before eating.

Mixing

While stirring, add up to 3.2 ounces of Rainguard® Slip Resist to one gallon of coating. Follow application instructions on paint or sealer. In thinner products, occasional stirring during use may be required to keep grit uniformly dispersed. Do not re-apply when wet. Wait until dry to apply a second coat if desired.

Mixing Ratio

Add 3.2 ounce bag of Slip Resist Anti-Slip Additive per 1 Gallon bottle 1:1

Add 16 ounce bag of Slip Resist Anti-Slip Additive for 1 Gallon per 5 Gallon pail 1:1

Warranties

Rainguard Brands, LLC guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. Rainguard Brands, LLC makes no other warranty, expressed or implied, and all warranties of merchantability and fitness for a particular purpose are hereby disclaimed. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product. Manufacturer shall not be liable for material used outside of its shelf life. For product dating, please refer to the batch number on the product or contact Rainguard Brands, LLC.

Surface conditions and application variables are out of the control of Rainguard Brands, LLC. As such, the applicator agrees to: Follow recommended application instructions, acknowledge limitations outlined in this technical data sheet, contact the manufacturer in the event there any uncertainties, perform a test panel to confirm fit and finish before any general application. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Rainguard Brands assumes no obligation or liability for use of this information. Contact manufacturer at 888-765-7070 before bidding to confirm warranty provisions and procedures.

SELLER'S LIABILITY UNDER THE SALE OF THIS PRODUCT IS LIMITED TO REPLACING DEFECTIVE PRODUCT. HOWEVER, IF SELLERS FAILS IN ITS ATTEMPT TO REPLACE THE DEFECTIVE PRODUCT, BUYER WILL BE ENTITLED TO A REFUND OF MONIES PAID TO SELLER UNDER THIS PRODUCT WARRANTY. SELLER IS NOT LIABLE FOR BUYER'S LOSS OF PROFITS, BUSINESS GOODWILL, OR OTHER CONSEQUENTIAL DAMAGES, DESPITE ANY FAILURE TO REPLACE THE PRODUCT. BUYER HAS ACCEPTED THIS RESTRICTION ON ITS RIGHT TO RECOVER CONSEQUENTIAL DAMAGES AS PART OF ITS BARGAIN WITH SELLER. BUYER REALIZES AND ACKNOWLEDGES THAT THE PRICE OF THE PRODUCT WOULD BE HIGHER IF SELLER WERE REQUIRED TO BE RESPONSIBLE FOR BUYER'S CONSEQUENTIAL DAMAGES."

© 2024 RAINGUARD BRANDS, LLC. All rights reserved.