See nothing, hear everything

Bass is a vital element in our enjoyment of sound. It's true for both music and movies, and it's as true for custom installation as it is for an audiophile's two-channel hi-fi. The ISW-3 is an incredibly versatile and compact in-wall and in-ceiling subwoofer, capable of providing high-quality bass output in spaces that may have previously missed out on this vital element, including kitchen cabinets! Its balanced design, featuring 2 x 6.5in drivers, means that it can be placed in a variety of locations without causing vibrations. Powered by a separate audiophile-standard 250W Class D amplifier the SA250 Mk2, the system keeps its cool even when you listening to demanding movie soundtracks at high volumes.

ISW-3 Technical Specifications

Drive units	2 x 165mm (6.5in) Paper/Kevlar® cone
Frequency range	-6dB at 21Hz and 222Hz adjustable (EQ at A)
Frequency response	±3dB 27Hz - 120Hz adjustable (EQ at A)
Bass extension	-6dB at 21Hz (position A) -6dB at 25Hz (position B) -6dB at 29Hz (position C)
Maximun Amp Power	250W
Impedance Nominal	8Ω (minimum 6.3Ω)
Dimensions	Width: 330mm (13in) Length: 470mm (18.5in) Depth: 235mm (9.25in)
Net weight	12.5kg
Electronics (mandatory)	SA250 Mk2

SA250 Mk2 Technical Specifications

Description	250W rack-mount amplifier with built-in subwoofer equalisation	**Input impedance**	33kΩ
Amplifier inputs	- 2x RCA Phono socket, line in - 2x RCA Phono socket, link out - 1x XLR socket, line in - 1x XLR socket, link out - 3.5mm jack - 12V trigger on/standby (overrides manual standby setting) - 3.5mm jack - 12V trigger equalisation movie/music	**Signal / noise**	>80dB
		Rated power consumption	95W – 1/8 full power 30W – Idling
		Dimensions	Height: 100mm (3.9 in) [88.5mm (3.5 in) plus feet] Width: 430mm (16.9 in) Depth: 322mm (12.7 in) Front panel Height: 2U 88.1mm/3.5 in
Amplifier outputs	- 1x Neutrik® Speakon® 4-pole speaker socket - 2x pairs of Binding Posts	**Net weight**	5.4kg (11.9 lb)
Amplifier power output	250W	**Finish**	Black