

ViewSonic® PROJECTOR

X1000-4K+

Key Features

- True 4K HDR visual experience
- Ultra Short Throw gives you a 100" screen from 38cm away
- Cinema SuperColor+™ Technology with 125% Rec.709
- 2nd generation LED Technology with 30,000 hours lifespan
- 40W Integrated Harman Kardon soundbar



Product Description

The ViewSonic X1000-4K+ Ultra Short Throw Smart LED Soundbar Projector delivers a completely immersive audiovisual experience right out of the box by fusing performance with elegance while melding into your modern lifestyle. Equipped with true 4K UHD resolution and 0.25 ultra-short throw ratio, the X1000-4K+ provides an impressive 100" image from a distance of only 38cm. Further features include 2nd generation LED technology with enhanced brightness, superior color display (125% Rec. 709), and a lifespan of 30,000 hours. An integrated 40W Harman Kardon-customized soundbar delivers room-filling crystal clear audio perfect for music and movies. The X1000-4K+ may be utilized as a Bluetooth soundbar or connected to a subwoofer to create a 2.1 audio system. Embedded Wi-Fi connectivity and built-in app center make streaming content easier than it's ever been before.



1. IR

8. Eye Protection Sensor

15. Wi-Fi Dongle

- | | | |
|--------------------------------|-------------------------------|------------------|
| 2. Adjustment Foot | 9. Lens | 16. AC In |
| 3. USB Reader (5V/2A, 5V/1.5A) | 10. Subwoofer Out / Audio Out | 17. Power Button |
| 4. USB Type-C (5V/2A) | 11. HDMI 2.0 / HDCP 2.2 | |
| 5. HDMI 2.0 / HDCP 2.2 | 12. LAN Control | |
| 6. Audio Out | 13. S/PDIF | |
| 7. Audio In | 14. Service | |

Visit Us

www.viewsonic.com

SPECIFICATION

| | |
|---|---|
| Native Resolution: | 3840x2160 |
| Brightness: | 2400 (LED Lumens) |
| Contrast Ratio: | 4,000,000:1 |
| Display Color: | 1.07 Billion Colors |
| Light Source Type: | LED |
| Light Source Life (hours) with Normal Mode: | up to 30000 |
| Lamp Watt: | RGBB LED |
| Lens: | F=1.91, f=2.51mm |
| Projection Offset: | 120%+/-5% |
| Throw Ratio: | 0.25 |
| Optical Zoom: | Fixed |
| Image Size: | 60"-150" |
| Throw Distance: | 0.159m-0.657m (100"@0.379m) |
| Keystone: | +/- 14° (V) |
| Audible Noise (Normal): | 25dB |
| Audible Noise (Eco): | 23dB |
| Local Storage: | Total 16GB (12GB available storage) |
| Input Lag: | 66ms |
| Resolution Support: | VGA(640 x 480) to 4K(3840 x 2160) |
| HDTV Compatibility: | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P |
| Horizontal Frequency: | 15K-135KHz |
| Vertical Scan Rate: | 23-120Hz |

INPUT

| | |
|------------------------|---|
| HDMI: | 3(HDMI 2.0, HDCP 1.4/2.2) |
| USB Type C: | 1 (5V/ 2A) |
| Audio-in (3.5mm): | 1 |
| Audio-in (Bluetooth): | 1 (BT4.0) |
| USB Type A: | 3(USB3.0 Reader x1, USB2.0 Reader x1, Wifi dongle x1) |
| RJ45 Input (Internet): | 1 |
| Wifi Input: | 1(5Gn) |

OUTPUT

| | |
|------------------------|--|
| Audio-out (3.5mm): | 2 (headphone x1, subwoofer x1) |
| Audio-out (Bluetooth): | 1 (BT4.0) |
| S/PDIF: | 1 |
| Speaker: | 20W Cube x2 |
| USB Type A (Power): | 3 (USB3.0 - 5V/2A x1, USB2.0 - 5V/1.53 (USB3.0 - 5V/2A x1, USB2.0 - 5V/1.5A x1, USB2.0 - 5V/900mA x1, share with USB A Input)A x1, USB2.0 - 5V/900mA x1, share with USB A Input) |

OTHERS

| | |
|--|---|
| Power Supply Voltage: | 100-240V+/- 10%, 50/60Hz(AC in) |
| Power Consumption: | Normal: 200W Standby: <0.5W |
| Operating Temperature: | 0~35°C |
| Net Weight: | 9.44kg |
| Dimensions (WxDxH) with Adjustment Foot: | 757x291x169mm |
| OSD Language: | English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages |

STANDARD ACCESSORY

| | |
|-----------------|---------------|
| Power Cord: | 1 |
| USB-C Cable: | 1 (1m) |
| Remote Control: | 1(w/ backlit) |
| QSG: | Yes |

CONTROL

| | |
|-----------------------------|---|
| USB Micro B-2.0 (Services): | 1 |
|-----------------------------|---|

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.