Network Camera


TVT-D2.8POE 5.0MP IP Dome Camera - 2.8mm Lens



- Vandal Dome
- Power Over Ethernet
- 20-30m Infrared Range
- IP67 For New Zealand Conditions
- 2 Year Return to Base Warranty









Network Camera

TVT-D2.8POE




5MP Network IR Waterproof Dome Camera


SPECIFICATIONS

Model Specifications	TVT-D2.8POE
Camera	
Image Sensor	1/2.7 "CMOS
Image Size	2592×1944
Electronic Shutter	1/25 s ~ 1/100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0236 lux @F2.0, AGC ON; 0 lux with IR 0.0085 lux @ F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F1.85, horizontal field of view: 93.4° 3.6 mm @F2.0, horizontal field of view: 79.4°
Lens Mount	M12
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
-	
Angle Adjustment	Pan: 0°~360°; Tilt:-0°~90°; Rotation: 0°~360°
Image	
Video Compression	H.265 / H.264
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	5MP (2592 × 1944), 4MP (2560 × 1440),1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream	60Hz:5MP(1~20fps)/4MP(1~30fps)/1080P(1~30fps)/ 720P(1~30fps)
	50Hz:5MP(1~20fps)/ 4MP(1~25fps)/1080P(1~25fps)/ 720P(1~25fps)
Sub Stream	60Hz:720P(1~15fps)/D1(1~30fps)/CIF(1~30fps); 50HZ:720P(1~12fps)/D1(1~25fps)/CIF(1~25fps)
Third Stream	60Hz : D1/CIF/480x240 (1~30fps); 50HZ: D1/CIF/480x240 (1~25fps
Bit Rate	64 Kbps ~ 5 Mbps
Bit Rate Type	VBR/CBR
Audio Compression	G711A/U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Video Output	No
Audio	1CH built-in MIC
	No
Storage	
Hardware Reset	No
Functions	Web beausing CMC corrects control
Remote Monitoring Online Connection	Web browsing,CMS remote control Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPs, QoS
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network remote storage
Smart Alarm	Motion detection
Intelligent Analytics	N/A
General Function	Watermark, IP address filtering, video mask, heartbeat, password protection
PoE	Yes
IR Distance	20 ~ 30 m
	IP67

Others	
Power Supply	DC12V/PoE
Power Consumption	< 5W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 108 × 95.7
Weight (net)	Approx. 0.47KG
Installation	Ceiling mounting; Wall mounting

DIMENSIONS





AVAILABLE ACCESSORIES







TD-YXH0103

TD-YXH0105









TD-YZH0205

TD-YZJ0203



TD-YXH0302+ TD-YZJ0407+TD-YZJ0501 TD-YXH0302+ TD-YZJ0407+TD-YZJ0601

