



5MP MOTORISED IR BULLET CAMERA



FGSIP-C5BMVA-2812

KEY FEATURES:

- Full metal housing
- Motorised lens 2.8-12mm
- Up to 2592x1944@20fps
- S+265/H.265/H.264/M-JPEG
- Min. illumination colour: 0.002Lux@F1.6
- 120dB WDR
- Smart IR, IR Range: 80m
- Support tripwire and perimeter
- Built-in mic, SD card slot, reset button
- Operating conditions -35° to 65°C, 0~95% RH
- POE, IP67

Starlight Technology

Incorporates FERN360 Starlight technology. When applied in low illuminance environments, FERN360 Starlight technology provides clear colour video. Even in ultra-low light situations, the technology will produce a superior quality video image

Intelligent Video Analytics (IVA)

Utilising an advanced video algorithm, this FERN360 camera supports intelligent detection, including tripwire and intrusion parameters.

Protection (IP67)

The camera enclosure has passed a series of strict tests in relation to its ability to protect the camera when exposed to dust and water.

Wide Dynamic Range (WDR)

FERN360 adopts advanced Wide Dynamic Range (WDR) technology. This enables clear images even in high-contrast environments with varying light levels.

Technical Specifications

Camera

Sensor	1/2.8" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color: 0.002Lux@ (F1.6, ACG ON), B/W: 0 Lux with IR
Shutter Time	1s to 1/100,000s
Day & Night	Dual IR Cut Filter with Auto Switch
Wide Dynamic Range	120dB
Angle Adjustment	Bracket, pan 0~360°, tilt 0~75°, rotate 0~360°

Lens

Lens Type	Motorised
Focus	2.8-12mm
Lens Mount	Φ14
Aperture	F1.6~F3.3, Fixed
FOV	Horizontal field of view: 100.4~26.8°

Illuminator

IR LEDs	4
IR Range	Up to 80m
Wavelength	850nm
White LEDs/Warmlights	N/A

Compression Standard

Video Compression	S+265/H.265/H.264
Video Bit Rate	32Kbps~6Mbps
Audio Compression	G.711/G.711U/ADPCM
Audio Bit Rate	8K~48Kbps

Image

Max. Resolution	2592x1944
Main Stream	PAL: 20fps (2592x1944) 25fps (2592x1520, 2560x1440, 2304x1296, 1920x1080, 1280x720)
	NTSC: 20fps (2592x1944) 25fps (2592x1520, 2560x1440), 30fps (2304x1296, 1920x1080, 1280x720)
	PAL: 25fps (704x576, 704x288, 640x360, 352x288)
	NTSC: 30fps (704x480, 704x240, 640x360, 352x240)
Sub Stream	
Third Stream	N/A
Image Setting	Saturation, brightness, contrast, sharpness, adjustable by client software or web browser
Image Enhancement	BLC/3D DNR/HLC/Corridor Format

ROI	N/A
OSD	16x16, 32x32, 48x48, adaptable size, Letters such as Week, Date, Time, Total 3 Regions
Picture Overlay	N/A
Privacy Mask	Yes, 4 regions
Smart Defog	Yes

Features

Alarm Trigger	Motion Detection, Mask Alarm, IP Address Conflict
Video Analytics	Tripwire, Perimeter
Early Warning (EW)	N/A

Network

ANR	Yes, auto store video in SD card when NVR disconnected, and upload video to NVR when resumed connection (Only Supports FERN360 ANR NVR)
Protocols	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet
System Compatibility	ONVIF (PROFILE S/T/G), SDK, CGI (IE), P2P (Mutually exclusive with Profile G)
Remote Connection	≤7
Client	Easy7, EasyLive
Web Version	Web5

Interface

Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio I/O	Mic in
Alarm I/O	N/A
Reset Button	Yes
On-board Storage	Built-in MicroSD card slot, up to 512 GB

General

Firmware Version	-
Web Client Language	15 languages English, Russian, Spanish, Korean, Italian, Turkish, Simple Chinese, Traditional Chinese, Thai, French, Polish, Dutch, Hebraism, Arabic, Vietnamese
Operating Conditions	-35°C ~ 65°C, 0 ~ 95% RH
Power Supply	DC 12V±25%/ PoE (802.3af)
Power Consumption	MAX: 9W (12V) MAX: 10W (PoE)
Protection	IP67, Lightning protection, surge protection and voltage transient protection meets EN 55035:2017
Heater	N/A
Dimensions	Φ239x90x90mm (Φ9.41x3.54x3.54inch)
Weight	0.93Kg (2.05lb)

5MP MOTORISED IR BULLET CAMERA | FGSIP-C5BMVA-2812

Ordering Information

Part Number	Description
FGSIP-BKPM-36	Pole Mount Bracket
FGSIP-BKCM-35	Corner Mount Bracket
FGSIP-BKJB-5	Surface Mount Junction Bracket

Accessories



FGSIP-BKCM-35



FGSIP-BKJB-5



FGSIP-BKPM-36

Dimensions

