

BRAND **PRIMACOL**[®] DECORATIVE

PRODUCT **Mystic**
Decorative paint for indoor use

- Effect of glittering crystals



PACK **1l**

PROPERTIES Mystic is a decorative paint for indoor use. Thousands of particles in the paint sparkle and glitter in the light to create a spectacular visual effect on the surface. Mystic is perfect for both modern and classic interiors. It will completely change the look of rooms. The product is available in a palette of ready colors.

Mystic paint is intended for painting surfaces of mineral and gypsum plaster, wooden and wood-based surfaces and fiberglass wallpapers.

APPLICATION Painting must be performed at the room and substrate temperature of 5-25 °C. Avoid direct sunlight on the surface being painted. Mix the paint thoroughly before use. Depending on the application technique, we can obtain two different decorative effects:

1. Shading/ rubbing effect

Apply the paint with a soft-pile, flat brush with cross movements. During application, the paint can be gently smoothed with a brush so as to obtain an even and smooth surface (Note! The paint is quick-drying). If needed, the second layer may be applied once the first one has dried (about 3 h) by using the same application technique.

2. Uniform effect

In order to obtain a uniform effect (without shades) , the paint must be applied by spray. However, it must be diluted with max 10% of water then filtered. After that, apply evenly 1 or 2 layer(s).

Note! Before working on the main surface, make a spot test to get acquainted with the application technique and check whether the effect is as desired. The manufacturer shall not be liable for any misuse of the product. For the entire surface, it is recommended to use products from the same production batch. Otherwise, mix the contents of all product packaging in one container. Once the job is finished, ventilate the room until the odour has gone.

SUBSTRATE PREPARATION The substrate should be durable, strong, dry, smooth, free of dust, residual adhesives and paints. Fresh plaster can be painted after 3-4 weeks of seasoning. Losses of material and cracks must be repaired and made even using filler putty. Prime absorptive substrates, for example using Primacol Decorative primer. In order to reduce product consumption, it is recommended to paint the substrate with a Decobase paint of a color similar to that of the effect (see the Decobase paint number on the lid).

STORAGE Store within the temperature range of 5-25 °C in dry area in the original, tightly closed container. Protect from frost and direct sunlight.

SAFETY Contains the reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazole 3 (2H) -one. May produce an allergic reaction. Keep the product out of reach of children. Detailed information included in the product safety data sheet.

TECHNICAL DATA

Chemical composition	polymer dispersion, mineral fillers, auxiliaries, pigments, brocades	Number of layers	2
Color	according to the color pattern	Application of successive layer	after 2-3h
Odor	mild, characteristic	Tools	flat brush,
pH	7,5-8,5	Tool cleaning	water
Density	1,1-1,2 g/cm ³	Thinner	water
Dry to touch	1-2 h	Efficiency per 1 layer	approx. 12 m ² /l
Completely dry	24 h	VOC limit	(Cat. A/I/WB)200g/l, product contains < 200 g/l

LEGAL INFORMATION The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.