

BRAND **PRIMACOL**<sup>®</sup> DECORATIVE

PRODUCT **Royal Silk**  
**Decorative paint for indoor use**

- Silk effect
- washable



PACK **1kg**

PROPERTIES High-quality paint for indoor use with a structure imitating the surface of silk fabric. Due to the presence of pearly filler material, the surface to be decorated obtains an effect of glimmering reflections that change with respect to the angle of light incidence. The paint is available in a palette of ready colours and as a base to be dyed using Primacol Decorative colorants. Once dried, it creates a durable and washable coating.

For use on cement, cement-lime substrates, gypsum boards and already painted surfaces.

APPLICATION Important! The product requires particular skills in application of such materials from the person performing the job. Before performing the proper job, make a spot test to become familiar with the application method and the visual effect that can be obtained. The manufacturer shall not be liable for any misuse of the product. For the entire surface, it is recommended to use products from the same batch. Otherwise, mix the contents of all product packaging in one container.

**Note!** The color presented on the packaging, due to printing limitations, should be treated as illustrative only and cannot constitute the basis for complaint. In order to check the color, ask for a sample-card available at the store.

1. In order to reduce product consumption, it is recommended to paint the substrate with a Decobase paint of a colour similar to that of the effect (see the Decobase paint number on the lid).
2. Apply a layer of Royal Silk paint on a dry surface using a Venetian trowel. Perform this step on small areas and in various directions to cover the entire surface. Thickness of the applied layer should not exceed 1 mm.
3. When the decoration is drying, smooth the surface using a trowel. Keep moving the trowel in various directions, and as a result metallic reflections will be obtained.
4. If necessary, once dried (after about 4 hours), apply another layer and proceed in the same way as for the first layer.
5. Once the product is applied, ventilate the room until the odour has gone. Full strength properties are obtained after 28 days.

SUBSTRATE PREPARATION The substrate should be cleaned of dirt and dust, degreased, even, dry, strong and crack-free. Remove residues of paints, wallpaper and unstable plaster. Patch any spalling. Freshly applied cement plaster and cement-lime plaster should be seasoned for at least 4 weeks.

**STORAGE** Store at 5-25°C, in a tightly closed, original container, in a dry place. Protect from sunlight. Protect from frost.

**SAFETY** Keep out of reach of children. The product contains 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazole 3 (2H) -one. May cause an allergic reaction.

**TECHNICAL DATA**

Composition	Water acrylic dispersion, pigments, special additives	Completely dry	24h
Form	Thick, liquid	Tools	Venetian trowel
Colour	Silver, gold	Tool cleaning	water with detergent
Odour	Mild, specific	Thinner	water
Number of layers	1-2	Efficiency per 1 layer	7-9 m <sup>2</sup> / kg
Application of successive layer	4h	VOC limit	(kat A/I/WB)200g/l, product contains < 200 g/l
Dry to touch	1-2		

**LEGAL INFORMATION** The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.