

BRAND	PRIMACOL [®] DECORATIVE
PRODUCT	SILVER SAND Decorative paint for indoor use <ul style="list-style-type: none">• Single- layer• Effect of the sand blown by the wind



PACK	1l
------	-----------

PROPERTIES	Structural paint used to obtain creative decorative effects. The surface coated with the paint glitters with pearly reflections in the light and creates a three-dimensional effect of depth. Perfect visual effects are obtained both in artificial and natural light. Silver Sand contains special structural additives which create the pattern of sand blown by the wind during paint application. The product is used for indoor walls and ceilings. It is perfect for living rooms and parlours, corridors as well as conference rooms, hotels and restaurants. With its original and fine texture, it will create a unique decoration of each room. The paint is available in a palette of ready colours and as a base to be dyed with Primacol Decorative colorants.
------------	--

APPLICATION	Painting must be performed at the temperature > 5 °C. Avoid direct sunlight on the surface being painted. Mix the paint thoroughly before use. Apply the product with a flat brush. Depending on the desired effect, painting can be done vertically, horizontally, crosswise, in the chevron pattern or an irregular pattern. The manner of painting determines the decorative effect to be obtained. The job must be performed in steps of approx. 1 m ² .
-------------	---

Important! Before performing the proper job, it is always recommended to make a spot test to become familiar with the application method and the visual effect. The manufacturer shall not be liable for any misuse of the product. For the entire surface, it is recommended to use products from the same production batch. Otherwise, mix the contents of all products in one container. Once the job is completed, ventilate the room until the odour is gone.

SUBSTRATE PREPARATION	The substrate should be durable, strong, dry, smooth, free of dust, residual adhesives and paints. Fresh plaster can be painted after 3-4 weeks of seasoning. Losses of material and cracks must be repaired and made even with filler putty. In order to reduce product consumption, it is recommended to paint the substrate with the Decobase paint of a colour similar to that of the effect (see the Decobase paint number on the lid).
-----------------------	--

STORAGE	Store at 5-25°C, in a tightly closed, original container, in a dry place. Protect from frost. Protect from direct sunlight. Once opened use within 4 days.
---------	--

SAFETY	Keep out of reach of children. The product contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazole 3 (2H) - one. May cause an allergic reaction
--------	---

TECHNICAL DATA

Chemical composition	Water acrylic dispersion, special additives, glass beads	Completely dry	min. 24h
Form	Thick liquid	Tools	Flat brush
Color	silver	Efficiency	10-15 m ² /l (depending on layer thickness and desired final effect)
Odour	Mild, specific	VOC limit	(Cat. A/l/WB) 200g/l, product contains < 200 g/l
Number of layers	1	Tool cleaning	water with detergent
Dry to touch	4-8 h	Solvent/ diluent	water

LEGAL INFORMATION The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.