

BRAND **PRIMACOL**[®] DECORATIVEPRODUCT **Concrete- look paint**

- Easy application
- Raw concrete effect
- Modern interior

PACK **8kg**

PROPERTIES A decorative paint based on mineral binder. Appropriate application provides the effect of vibrated concrete (smooth, glossy), as well as a surface with characteristic roughness, spalling, and pitting. It is perfect for modern interiors of public and residential buildings, in particular, for industrially arranged buildings. It is perfectly suitable for wood, glass, and glossy metal. It masks small surface imperfections.

APPLICATION The job must be performed at the temperature > 5°C and away from any intense heat sources. Avoid uneven and too quick paint drying. Control the degree of paint drying and add paint locally if required.

Before use, mix the product well. During application, stir the paint frequently. Apply the paint with a roller within an area up to 1 m² and smooth with a trowel. It allows working on a sufficiently wet surface that can be shaped. Before the paint dries, smooth it with a plastic trowel. Repeat it until the entire surface to be decorated is covered. Then leave the wall to dry for approximately 24 hours. After this time, apply the paint again with a roller within an area up to 1 m², leaving small holes in some places. Before the paint dries, gently smooth the painted surface with a plastic float. Repeat the operation until the entire surface is covered. After about 15-20 minutes make sure that the material on the wall is dry enough that it does not stick to the tools, take a Venetian trowel and, applying it flat with circular movements, smooth the decorated area once again. It will allow the paint grains to align resulting in effective leveling of any unevenness. Only small cavities, characteristic of concrete, will remain on the surface. Leave the wall to dry for 24 h.

Once the surface is dry, clean it with a brush to remove loose paint residues. Then apply Primacol Decorative varnish with a brush or a roller. When applying the varnish, pay special attention not to leave stains that will negatively affect the final visual effect. Repeat if necessary and allow the wall to dry for 24 hours. The decorative effect is ready after this time.

The concrete-look paint allows obtaining various decorative effects, depending on the application method and painter's imagination.

The final effect largely depends on painter's skills. The manufacturer shall not be liable for any damage caused by product misuse. Before the proper job, make a spot test.

For the entire surface, it is recommended to use products from the same batch. Otherwise, mix the contents of all product packaging in one container. Due to limitations of printing technology, the presented colour should be considered as illustrative only and cannot constitute the basis for complaint. In order to check the color, ask for a sample-card available at the store.

Efficiency of Concrete-Look Paint depends on surface absorptivity and preparation, thickness of applied layers, the effect to be obtained, and the painter's work.

SUBSTRATE

PREPARATION

The substrate should be dry, dust-free, degreased and free of any other dirt. Remove residual paint, plaster, and layers unbounded with the substrate and even the substrate. Then, using a roller, prime the entire surface with at least one layer of Kontakt grunt Primacol Decorative primer. It contains quartz sand in its composition, thanks to which the obtained coating is rough, which significantly increases the strength of the bond with the layer of Concrete Paint. Leave the prepared surface to dry for 12 hours. Concrete paint can be used on cement, lime and cement-lime plasters and after appropriate preparation for plasterboards.

Important! The concrete-look paint does not tolerate gypsum. For gypsum plaster or all surfaces containing gypsum, e.g. repairs with gypsum fillers, it is necessary to apply two layers of Kontakt Grunt in order to insulate the surface.

STORAGE

Store within the temperature range of 5-25°C in a tightly closed, original container. Protect from direct sunlight.

SAFETY

Keep out of reach of children. If swallowed, seek medical advice immediately and show this container or label. Protect from sunlight.

TECHNICAL DATA

Tools	Roller, plastic or Venetian float	Dry to touch	30-60 minutes (depending on layer thickness)
Color / odor	Grey / Specific	Completely dry	24 h
pH	>12	Efficiency per 2 layers	4 m ² per packaging
Density	Approx.1,55 – 1,65 g/cm ³	Diluent	Water
Number of layers	2	Tool cleaning	Water
Application of successive layer	2-4 h or 12-24	VOC limit	product contains < 200 g/l (cat. A/I/WB)200g/l

LEGAL INFORMATION

The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.