

BRAND **PRIMACOL® DECORATIVE**

PRODUCT **Metaliq Patine**
Surface patination paint

- Steel wall efet



PACK **0,5 kg**

PROPERTIES Decorative paste in ready-to-use colour to create a patinated effect on the surface. It is applied between **Metaliq Paste** and **Metaliq Top**.

SUBSTRATE PREPARATION The substrate to be decorated with Metaliq Patine should be prepared with Decobase paint and Metaliq Paste as described in Metaliq Paste.

APPLICATION Mix the product thoroughly. Apply it with a Venetian trowel to the dry Metaliq Paste surface. Apply a small amount selectively and in a thin layer. After 12 hours, wipe the surface with fine sandpaper and dedust it. Shine the effect with a clean spatula. Apply Metaliq Top in a selected color.

Always test the product on the main surface before use. The effect obtained depends on many factors, such as the preparation of the substrate, the tools used, the application technique.

STORAGE Store the product in a tightly closed original container at 5 - 30°C and out of the reach of children. Do not expose it to sunlight. Protect from freezing.

SAFETY Product treated with biocidal product. Contains C(M) IT /MIT (3:1). Contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

TECHNICAL DATA

Chemical composition	Water, polymer solution, fillers, additives	Tools	Steel float
Color	Green	Touch dry	1-2 h
Odour	Mild, characteristic	Completely dry	24 h
Density	1,70 kg/dm ³	Coverage per packaging	+/- 10m ²
Finish	Matte/ semi-matte/ gloss (depending on the application technique)	Diluent	Water
Number of layers	1	Tool cleaning	Water with detergent

VOC limit

(cat. A/l/FW): 200 g/l, the
product contains max. 200 g/l.

LEGAL INFORMATION

The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.