

POLARIS

## **TECHNICAL DATA SHEET**

UPDATE: 18.02.2022

BRAND	PRIMACOL® DECORATIVE		
PRODUCT	Polaris   Decorative paint for interiors   • Ice crystal effect		
РАСК	11		
PROPERTIES	A decorative paint for interior use. It creates a satin finish that shimmers with delicate reflections. The intensity of the effect increases with the intensity of the light source. It is perfect for modern, industrial and glamorous interiors.		
SUBSTRATE PREPARATION	The substrate should be clean, degreased, even, stable and not cracked. Fresh cement and lime-cement plasters should be seasoned for at least 4 weeks. The surface should be primed with <b>PRIMACOL® DECORATIVE primer</b> . To reduce the consumption of <b>Polaris</b> , it is recommended to paint the substrate with <b>Decobase</b> paint in a colour similar to the colour of the effect (see colour number on the lid). When dry, wipe the wall lightly with fine sandpaper and dedust it.		
APPLICATION	After opening the bucket it is necessary to mix the contents thoroughly. Start applying the product at the top corner of the wall and move diagonally to extend the decorated area. Apply the paint to the surface with a Venetian trowel in different directions. Do this in small areas and join successive elements using the "wet-on-wet" method. The thickness of the applied layer should not exceed 1 mm. Smooth the surface with the edge of a clean Venetian trowel in different directions before it dries completely. This will accentuate the decorative effect, especially the satin reflections. Repeat the process until the desired decorative effect is achieved. If necessary, you can apply a second coat of paint.		
	In order to obtain a coating that is resistant to washing, after drying, apply the PRIMACOL® DECORATIVE satin stain to the wall, which may darken the decorative effect.		
	<ul><li>NOTE! Tools should be washed frequently during work to avoid scratches on the decorated surface caused by the residue of the dried product.</li><li>It is recommended to decorate the surface with products from one production batch. Otherwise, the contents of all packages must be mixed together in one container.</li><li>Always test the product on the main surface before use. The effect obtained depends on many factors, such as the preparation of the substrate, the tools used, the application technique. The manufacturer accepts no responsibility for improper use of the product.</li></ul>		



## POLARIS

**TECHNICAL DATA SHEET** 

UPDATE: 18.02.2022

STORAGE	The product should be stored in a tightly closed original container at 5-30°C and out of the reach of children. Do not expose it to sunlight. Protect from freezing.			
SAFETY	Product treated with biocidal product. Contains C(M) IT /MIT (3:1). Contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Keep out of reach of children.			
TECHNICAL DATA				
Chemical composition	Acrylic dispersion, fillers, auxiliaries, pigments	Touch dry	1-2 h	
Color/ Finish	Dense emulsion, satin- pearl finish	Completely dry	24 h (depending on the layer thickness and drying conditions)	
Odour	Mild, characteristic	Efficiency per 1 layer	7 m <sup>2</sup> /l (depending on the layer thickness)	
рН	7,0-8,0	Diluent	Water	
Density	1,1 g/cm <sup>3</sup>	Tool cleaning	Warm water with detergent	
Number of layers	1 -2 (depending on the effect)	Voc limit	(cat. A/l/WB): 200 g/l, the product contains < 200 g/l.	
Tools	Venetian trowel			

LEGAL INFORMATION The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.