

ATTO MOBILITY SCOOTER

Flight Safety Certificates

LITHIUM-ION BATTERY 249.6 Wh

DRY, NON SPILLABLE

Battery dimensions: 32x 14x 1 1cm Weight 1.8kg

Page	Document	Standard / Doc
2	OVERVIEW	FDA / CE
3-22	BATTERY SAFETY DATA SHEET	MSDS
23	Scooter dimensions	



Take to hirport



MATERIAL SAFETY DATA SHEET

Rechargeable Li-ion Battery

Model: zn13s2p

Prepared by	Approved by
Simon Lu	Zhang hang
Jul 9,2019	Jul 9,2019

Material Safety Data Sheet

Section 1 - Chemical Product and Company Identification

Chemical Product Identification Sample Description: Rechargeable Li-ion Battery Sample Model: zn13s2p Recommended Uses: N/A Restrictions on Use: N/A Supplier Name: Shenzhen Zhuoneng New Energy Corporation Limited Address: Room 101, 201, 301 of Bld A;Bld B;Bld D.Bld G No.1, Sifangpu Village, Nianfeng Community, Pingdi , Longgang District, Shenzhen, P. R. China Phone Number: 0755-36518101 FAX: 0755-36518101 E-mail: renzheng@szznp.com Emergency Phone Number: 0755-36518101

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxiclty, oral (4) Skin corroslon/irritation (2) Serious eye damage/eye irritation (2A) Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements Hazard pictogram(s);

Signal word:

Hazard statement(s): VVa H302 Harmful if swallowed H315 Causes skin irritation H319 Causes serious eye irritation H335 May cause respiratory irritation



Waming

Precautionary statement(s):

Prevention:

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty water.

P321 Specific treatment (See additional emergency instructions).

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER, if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10 Human health hazards: See Section 11 Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chamical Composition		F0#	M_{a} and M_{a}
Chemical Composition	CAS No.	EC#	Weight (%)
Cobaltate, lithium	12190-79-3	235-362-0	30-60
Graphite	7782-42-5	231-955-3	10-30
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	10-30
Copper	7440-50-8	231-159-6	5-10
Aluminium	7429-90-5	231-072-3	1-5

Chemical characterization: Mixture

Nickel	7440-02-0	231-111-4	1-5
Polyvinyl chloride resin	9002-86-2	618-338-8	1-5

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse

thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention. **After inhalation**

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available. Most important symptoms/effects, acute and delayed: No data available. Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, CO, water spray or regular foam. **Large Fire:** Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150 (302)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handing must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to

fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control paramet	ers		
CAS No.	ACGIH	NIOSH	OSHA
12190-79-3	N/A	N/A	N/A
7782-42-5	TLV-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf
			PEL-TWA 20mppcf
21324-40-3	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m ³	REL-TWA 1mg/m ³	PEL-TWA 0.1mg/m ³
	TLV-TWA 1mg/m ³	REL-TWA 0.1mg/m ³	PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 1mg/m ³	REL-TWA 2mg/m ³	PEL-TWA 5mg/m ³
		REL-TWA 5mg/m ³	PEL-TWA 15mg/m ³
		REL-TWA 10mg/m ³	
7440-02-0	TLV-TWA 1.5mg/m ³	REL-TWA 0.015mg/m ³	PEL-TWA 1mg/m ³
9002-86-2	N/A	N/A	N/A

Control parameters

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact. Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and	chemical properties
Colour:	Black.
Physical State:	Prismatic.
Odour:	Not available.
Odour threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.

Initial boiling point and boiling range: Flash Point: Evaporation rate: Flammability (solid, gas): Explosion Limits (vol% in air): Vapour pressure, kPa at 20 : Vapor density: Density/Relative density (water = 1): Solubility(ies): Partition coefficient: n-octanol/water: Auto-ignition temperature:	Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available.
Decomposition temperature: Viscosity:	Not available. Not available.
Other information:	
Voltage	48V
Electric capacity	5.2Ah
Electric Energy	249.6Wh

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute	Toxicity:
-------	-----------

,	
CAS No.	LC50/LD50
12190-79-3	No data available.

7782-42-5	No data available.
21324-40-3	No data available.
7440-50-8	No data available.
7429-90-5	No data available.
7440-02-0	LD50 Rat (oral): >9000mg/kg
9002-86-2	No data available.

Skin corrosion/irritation:	No data available.
Serious eye damage/irritation:	No data available.
Respiratory or Skin sensitization:	No data available.
Germ Cell mutagenicity:	No data available.
Carcinogenicity:	No data available.
Reproductive toxicity:	No data available.
Specific target organ toxicity-Single exposure:	No data available.
Specific target organ toxicity-Repeated exposure:	No data available.
Aspiration hazard:	No data available.
Information on the likely routes of exposure:	No data available.
Eye:	No data available.
Skin:	No data available.
Ingestion:	No data available.
Inhalation:	No data available.

Section 12 - Ecological Information

Ecological Toxicity:
Persistence and degradability:
Bioaccumulative Potential:
Mobility in Soil:
Other adverse effects:

No data available. No data available. No data available. No data available. No data available.

Section 13 - Disposal Considerations

Disposal methods: Recommendation: Consult state, local or national regulations to ensure proper disposal. Uncleaned packaging Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN Number			
ΙΑΤΑ	UN3480 UN3481 UN3171		
IMDG	UN3480 UN3481 UN3171		
UN Proper shipping name			
ΙΑΤΑ	Lithium ion batteries		
	Lithium ion batteries packed with equipment		
	Battery-powered vehicle		
IMDG	LITHIUM ION BATTERIES		
	LITHIUM ION BATTERIES PACKED WITH EQUIPMENT		
	BATTERY-POWERED VEHICLE		
Transport hazard class(es)			
ΙΑΤΑ	9		
IMDG	9		
Packing group			
ΙΑΤΑ	N/A		
IMDG	N/A		
Packaging Sign			
IATA IMDG			
	965,966: 952:		
Environmental hazards			
Marine pollutant:	No		
Special precautions for user	No information available.		

Transport information: The Rechargeable Li-ion Battery zn13s2p has passed the test UN38.3, according to the report ID: MNI2OUHT00381721.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 965 section IA of |ATA DGR 60 Edition for transportation, Cargo aircraft only.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 966 section I of IATA DGR 60th Edition for transportation, Be shipped by passenger and cargo aircraft.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are

packaged according to the special provision 230, 348, 384 of IMDG (38-16).

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 952 of IATA DGR 60 Edition for transportation, Be shipped by passenger and cargo aircraft.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 240, 971of IMDG (38-16).

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Note: State of Charge (SoC) not exceeding 30% of their rated capacity. (By air, Lithium ion batteries)

Note: Batteries weight in the package 5kg. (By air, Batteries packed with equipment) Transport Fashion: By air, by sea.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or Mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
12190-79-3	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
7440-02-0	Listed	Listed	Listed DSL	Listed
9002-86-2	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Date: 2019-09-27 Issue Department: Technical department Modification record: Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);

PEL: (Permissible Exposure Level);

REL: (Recommended Exposure Limit);

PC-STEL: (Permissible concentration-short time exposure limit);

PC-TWA: (Permissible concentration-time weighted average);

LC50: (Lethal concentration, 50 percent kill);

LD50: (Lethal dose, 50 percent kill);

IARC: (International Agency for Research on Cancer);

EC50: (Median effective concentration);

BCF: (Bioconcentration Factor);

BOD: (Biochemical oxygen demand);

NOEC: (No observed effect concentration);

NTP: (US National Toxicology Program);

RTECS: (Registry of Toxic Effects of Chemical Substances);

IATA: (International Air Transport Association);

IMDG: (International Maritime Dangerous Goods);

TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);

TOC: (Total Organic Carbon);

TSCA: (Toxic Substances Control Act of USA);

DSL: (the Domestic Substances List of Canada);

NDSL: (the Non-domestic Substances List of Canada)

End of report

MATERIAL SAFETY DATA SHEET

Reference to ST/SG/AC.10/30/Rev.7(GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification Sample Description: Rechargeable Li-ion Battery Pack Sample Model: zn13s2p Recommended Uses: N/A Restrictions on Use: N/A Manufacturer: Guangxi Ares Energy Technology Co.,Ltd Address: Standard Workshop,Building A8,Industrial Investment (Jiangnan) Enterprise Company,No.12 Xiajin Road,Jiangnan District,Nanning, P. R. China Phone Number: 0771-3388317 FAX: / E-mail: renzheng@szznp.com Emergency Phone Number: 0771-3388317

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxiclty, oral (4)

Skin corroslon/irritation (2)

Serious eye damage/eye irritation (2A)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements

Hazard pictogram(s);

Signal word:

Hazard statement(s):

H302 Harmful if swallowed H315 Causes skin irritation

H315 Causes skill initiation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

Precautionary statement(s):

Prevention:

P264 Wash skin and clothing thoroughly after handling.

Waming

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty water.

P321 Specific treatment (See additional emergency instructions).

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER, if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chemical	characterization:	Mixture
----------	-------------------	---------

Chemical Composition	CAS No.	EC#	Weight (%)
Cobaltate, lithium	12190-79-3	235-362-0	30-60
Graphite	7782-42-5	231-955-3	10-30
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	10-30
Copper	7440-50-8	231-159-6	5-10
Aluminium	7429-90-5	231-072-3	1-5
Nickel	7440-02-0	231-111-4	1-5
Polyvinyl chloride resin	9002-86-2	618-338-8	1-5

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, CO_2 , water spray or regular foam. **Large Fire:** Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media: No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C(302 °F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handing must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
12190-79-3	N/A	N/A	N/A

7782-42-5	TLV-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf
			PEL-TWA 20mppcf
21324-40-3	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m ³	REL-TWA 1mg/m ³	PEL-TWA 0.1mg/m ³
	TLV-TWA 1mg/m ³	REL-TWA 0.1mg/m ³	PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 1mg/m ³	REL-TWA 2mg/m ³	PEL-TWA 5mg/m ³
		REL-TWA 5mg/m ³	PEL-TWA 15mg/m ³
		REL-TWA 10mg/m ³	
7440-02-0	TLV-TWA 1.5mg/m ³	REL-TWA 0.015mg/m ³	PEL-TWA 1mg/m ³
9002-86-2	N/A	N/A	N/A

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact. **Eye Protection:** Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties Colour: Black. **Physical State :** Almost Cuboid . Odour : Not available. **Odour threshold :** Not available. Not available. pH: Melting point/freezing point : Not available. Initial boiling point and boiling range: Not available. Flash Point : Not available. Not available. **Evaporation rate :** Not available. Flammability (solid, gas): Explosion Limits (vol% in air): Not available. apour pressure, kPa at 20 : Not available. Vapor density : Not available.

Density/Relative density (water = 1): Solubility(ies) : Partition coefficient: n-octanol/water : Auto-ignition temperature : Decomposition temperature : Viscosity : Other information:		Not available. Not available. Not available. Not available. Not available. Not available.
Voltage	48V	
Electric capacity	5.2Ah	
Electric Energy	249.6Wh	

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50	
12190-79-3	No data available.	
7782-42-5	No data available.	
21324-40-3	No data available.	
7440-50-8	No data available.	
7429-90-5	No data available.	
7440-02-0	LD50 Rat (oral): >9000mg/kg	
9002-86-2	No data available.	

Skin corrosion/irritation :

Serious eye damage/irritation :

No data available. No data available.

Respiratory or Skin sensitization :	No d
Germ Cell mutagenicity :	No c
Carcinogenicity :	No d
Reproductive toxicity :	No c
Specific target organ toxicity-Single exposure:	No d
Specific target organ toxicity-Repeated exposure:	No d
Aspiration hazard :	No d
Information on the likely routes of exposure:	No d
Eye :	No d
Skin :	No d
Ingestion :	No d
Inhalation :	No d

No data available. No data available.

Section 12 - Ecological Information

Ecological Toxicity : Persistence and degradability : Bioaccumulative Potential : Mobility in Soil : Other adverse effects : No data available. No data available. No data available. No data available. No data available.

Section 13 - Disposal Considerations

Disposal methods: Recommendation: Consult state, local or national regulations to ensure proper disposal. Uncleaned packaging Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN Number	
IATA	UN3480 UN3481 UN3171
IMDG	UN3480 UN3481 UN3171
UN Proper shipping name	

ΙΑΤΑ	Lithium ion batteries	
	Lithium ion batteries packed with equipment	
	Battery-powered vehicle	
IMDG	LITHIUM ION BATTERIES	
	LITHIUM ION BATTERIES PACKED WITH EQUIPMENT	
	BATTERY-POWERED VEHICLE	
Transport hazard class(es)		
IATA	9	
IMDG	9	
Packing group		
ΙΑΤΑ	N/A	
IMDG	N/A	
Packaging Sign		
IATA	ath, ath,	
IMDG	· · · · · · · · · · · · · · · · · · ·	
	965,966: 952:	
Environmental hazards		
Marine pollutant :	No	
Special precautions for user	No information available.	

Transport information: The Rechargeable Li-ion Battery zn13s2p has passed the test UN38.3.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 965 section IA of IATA DGR 60th Edition for transportation, Cargo aircraft only.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 966 section I of IATA DGR 60th Edition for transportation, Be shipped by passenger and cargo aircraft.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 230, 348, 384 of IMDG (38-16).

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 952 of IATA DGR 60th Edition for transportation, Be shipped by passenger and cargo aircraft.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 240, 971of IMDG (38-16).

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Note: State of Charge (SoC) not exceeding 30% of their rated capacity. (By air, Lithium ion batteries) Note: Batteries weight in the package < 5kg. (By air, Batteries packed with equipment) Transport Fashion: By air, by sea.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or Mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
12190-79-3	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
7440-02-0	Listed	Listed	Listed DSL	Listed
9002-86-2	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Date: 2022-12-01 Issue Department : : Technical department Modification record : Notice to reader

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide.

The information and recommendations set forth are made in good faith and believed to

be accurate as of the date of preparation. Guangxi Ares Energy Technology Co., Ltd. makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

End of report

Scooter Sizes & Dimensions

• For sending to the cargo bay:

In trolley mode (folded, as shown in picture) 72x42x39 cm



For more information please contact Moving Life



USA +1-347-761-3317 UK +44-(0)20-3769 7530 Israel +972-(0)73-391 3999



info@movinglife.com



All Rights Reserved © 2016-2017 Moving Life Ltd. RG-039-ATTO- Flight Safety Certificates-Ver 3.7