



Technical Data Sheet

Description:

Fabric is woven from 100% highly texturized Fiberglass yarn, Designed as a replacement for Asbestos Textiles

Application:

Safety apparel, Fire Blankets, Curtains, Safety Barriers, Heat Insulation Pads, Pipe wrap.

Technical Data:

Physical Properties:

Weight	17.5 oz/sq yd
Construction	Warp – 20 Fill – 14
Weave	Plain
Thickness	.030"
Temperature	1000°F (538°C)
Tensile Strength	Warp – 200 lbs Fill – 100 lbs

Chemical Resistance:

Resists Most Acids Alkalies and Solvents, with the exception of Hydroflouric Acid and corrosive Environments at elevated temperatures.

Availability:

50 Yards/Roll

40" & 60" Wide

Specifications:

Meets Military Specification MIL-1-24244, and U.S Coast Guard Spec. CFR-164.009. also Mil Spec. MIL-C-0020079F(SH) Type 1, Class 9.



Toronto • Montreal
www.specialtygaskets.com

DISCLAIMER: The information in this Technical Data Sheet is believed to be correct as of the date issued. Specialty Gaskets Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Specialty Gaskets Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Specialty Gaskets Inc. Product it is essential that the user evaluate the Specialty Gaskets Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.



ISO 9001