



Technical Data Sheet

Description:

EPDM is a polymer that provides superior properties for outdoor and high ozone environment applications. EPDM rubber also provides better resistance to acids, alkali and ketones than other general rubber sheets. EPDM sheet is commonly used for roofing, automotive and other applications where high temperature (up to 248°F) is required. However, EPDM sheet has poor resistance to fuels, oils and alcohols.

Physical Properties	
Hardness (60 Shore A)	+/- 5
Tensile Strength (psi)	725
Elongation at Break (%)	500
Temperature Range (°F)	-22 to 220
Temperature Range (°C)	-30 to 104



Toronto • Montreal
www.specialtygaskets.com

DISCLAIMER: The information in this Technical Data Sheet is believed to be correct as of the date issued. Specialty Gaskets Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Specialty Gaskets Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Specialty Gaskets Inc. Product it is essential that the user evaluate the Specialty Gaskets Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.



ISO 9001