

# ANDEROL PRODUCT DATA SHEET

## ANDEROL® 755

SYNTHETIC COMPRESSOR LUBRICANT

### GENERAL INFORMATION

ANDEROL 755 is an ISO 150 diester based synthetic compressor lubricant specifically designed to provide long-term lubrication in process gas compressors.

### TYPICAL PROPERTIES:

SALES SPECIFICATIONS				
PROPERTY	TEST METHOD	MIN	MAX	TYPICAL
Viscosity @ 40°C, cSt	ASTM D-445	135	165	147
Viscosity @ 100°C, cSt	ASTM D-445	12.5	14.5	13.3
Pour Point, °C	ASTM D-97	-	-30	-37
Flash Point, °C	ASTM D-92	240	-	270
Specific Gravity, 15.6°C	ASTM D-4052B	0.95	0.97	0.96

ADDITIONAL INFORMATION		
PROPERTY	TEST METHOD	TYPICAL
Autoignition Temperature, °C	ASTM E-659	410
Conradson Carbon Residue, %	ASTM D-189	0.02
Evaporation, 22 hrs @ 99°C, %	ASTM D-972	<1.0
Copper Strip Corrosion, 3 hrs @ 100°C	ASTM D-130	1A
Demulsibility @ 54°C, ml oil/water/emulsion (min)	ASTM D-1401	39/38/3 (<60)
Four-Ball Wear, 1200 rpm, 75°C, 40 kg, 1 hr, mm	ASTM D-2266	0.8

**ANDEROL 755**

®ANDEROL is a reg. trademark of ANDEROL COMPANY.

**For more information please refer to the relevant Material Safety Data Sheet accompanying each product.**

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only chemists or chemically qualified lab technicians should carry out tests. Before using any chemical, read its label and Material Safety Data Sheet.

## APPLICATIONS

For cylinder and frame lubrication of reciprocating compressors and vacuum pumps using the following gases:

Air	Butadiene	Carbon Dioxide (dry)	Carbon Monoxide
Ethylene	Furnace (crack) Gas	Helium	Hydrogen
Hydrogen Sulfide (dry)	Methane	Natural Gas	Nitrogen
Propane	Sulfur Hexafluoride	Synthesis Gas	

Nominal Operating Range is  $-15^{\circ}\text{C}$  to  $230^{\circ}\text{C}$  ( $5^{\circ}\text{F}$  to  $450^{\circ}\text{F}$ ).

## ADVANTAGES

- Fewer oil changes
- Reduces compressor maintenance
- Greatly reduces fire and Explosion hazard
- Separates water condensate rapidly
- Lower oil consumption
- Eliminates lacquering and deposits
- Reduces energy consumption
- 

## COMPATIBILITY

COMPATIBILITY - The following seals, paints, and plastics are recommended for use in contact with Anderol Company Synthetic Lubricants. Materials not recommended are also shown. For more information on other materials, see our "Compatibility Guide."

RECOMMENDED - Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

NOT RECOMMENDED - Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS

A755: 3/14/01eb



ANDEROL COMPANY  
PO Box 518, 215 Merry Lane  
East Hanover, New Jersey USA  
Tel: 888-ANDEROL  
Or Tel: (973) 887-7410  
Fax: (973) 884-3825  
E-mail: info2@anderol.com