



WANDERSOFT Portable RV Water Softener Owner's Manual



FEATURES OF YOUR WANDERSOFT PORTABLE SOFTENER

Congratulations on the purchase of your new WANDERSOFT Portable Water Softener.

You will have the peace of mind knowing your USA Designed and Assembled system will bring you years of treated water use and enjoyment, wherever the road may take you!

Your new system will help you:

Eliminate:

- Scale Deposits
- Soap Scum
- Dissolved Minerals on Fixtures
- Stains

Enjoy:

- Soft water in remote places
- Better soap lathering
- Cleaner dishes
- Softer Skin
- Scale free coffee pots
- Clog free showerheads



How To Use This Manual


This owner's manual is designed to provide the product owner with instructions on performing routine care, maintenance and installation of the WANDERSOFT Portable Water Softener packaged with this manual.

This manual does not include instructions regarding service or troubleshooting of the product. Please contact Affordablewater.us directly at 877-848-2532 or support@affordablewater.us with questions or concerns about the operation or performance of your portable water conditioning system.

Icons That Appear In This Manual

 **WARNING!** Failure to follow instructions can result in personal injury or damage to the equipment.

General Warnings

 **WARNING!** There are no user-serviceable parts in the WANDERSOFT Portable Water Softener. Do not attempt to remove or repair individual components.


 **WARNING!** Maximum Operating Pressure is 150 PSI/10.3 BAR/1030 kPa

 **WARNING!** Operating Temperature is 34F (1.1C) to 120F (49C)

 **WARNING!** Do not expose vessel to temperatures below -20F (-29C)

 **WARNING!** Do not use for pneumatic or hydro-pneumatic applications. Maximum Negative Pressure is 5" Hg (127mm Hg)

California Proposition 65 Warning

 **WARNING!** This product contains chemicals known to the State of California to cause cancer or birth defects or other reproductive harm.

INSTALLING YOUR WANDERSOFT

Your WANDERSOFT Portable Water Softener comes charged and ready to use out of the box! Once you hook up the softener, you will have soft water until it is time to regenerate the unit.

1. Hook up the supplied 4' drinking water hose to the OUTLET Side of the WANDERSOFT manifold. Direct the hose to a drain or an area outside where water can drain.
2. Hook the incoming water supply line to the Inlet Side of the WANDERSOFT manifold. Slowly turn on the water supply, and let the water run through the unit for 4-6 minutes to prime the unit and rinse the resin of any remaining coloration.
3. Turn the incoming water supply off. Connect the 4' hose from the OUTLET side of the WANDERSOFT manifold to your vehicle's incoming water port.
4. Enjoy the many benefits of soft water on the road!



REGENERATING YOUR WANDERSOFT

Our 12,000 Grain WANDERSOFT Portable Water Softener is capable of softening approximately 600 gallons of water at 20 GPG hardness, which is an average water hardness in many locations throughout the United States. Our 8,000 Grain model is capable of softening approximately 400 gallons of water at 20 GPG hardness.

It is time to regenerate your WANDERSOFT when you begin to notice the adverse effects of hard water. The first things you will begin to see are scale buildup on your fixtures, and soap that doesn't lather as well. Use the included Soap Test Kit to confirm a lack of soft water.

Your WANDERSOFT can be regenerated with a standard four pound box of table salt.



WARNING! DO NOT USE ROCK SALT OR WATER SOFTENING SALT, AS THE GRANUALS ARE TOO LARGE TO WORK EFFECTIVELY USING THIS METHOD OF REGENERATION!

Regeneration Instructions

1. Turn off water supply, then relieve pressure from system. Unhook outlet line and direct hose to drain, bucket or other location where water can drain.
2. Remove salt-fill cap from top manifold. Remove a small amount of water from tank to make room for salt.
3. Pour in a four pound box of TABLE SALT.
4. Clean salt-fill port threads and replace salt-fill cap. DO NOT OVERTIGHTEN.
5. Turn on the water supply and let the softener run SLOWLY to the drain or bucket for approximately 10 minutes or until water runs clear with no salt taste.
6. Reconnect outlet line. Your softener is now ready to use again!

STORING YOUR WANDERSOFT

When adventuring time is done and it is time to winterize your vehicle, don't neglect to take appropriate steps to winterize your WANDERSOFT as well.

To store your WANDERSOFT when not in use, completely disconnect the unit from all water supply hoses, and remove all the water from inside the unit to prevent freezing.

Although the WANDERSOFT must be vertical when in use, the unit may be stored either horizontally or vertically while disconnected.

If your WANDERSOFT was stored for an extended period of time, sanitize the unit with a capful of hydrogen peroxide when being put back into service. Simply add the hydrogen peroxide through the salt-fill port, and slowly rinse the softener for 4-6 minutes prior to use.



This Page Intentionally Left Blank



The WANDERSOFT Portable RV Water Softener comes with a 1 year manufacturer warranty. Please contact Affordablewater.us for questions or concerns.



3211 Dryden Rd. | Dayton, OH 45439 | United States
P: 877-848-2532 | support@affordablewater.us | affordablewater.us

All Affordablewater trademarks and logos are property of Affordablewater.us, All rights reserved.