PENDANT PUSHBUTTON STATIONS

SBP2® PENDANT PUSHBUTTON STATIONS

- Provide optimum control and performance for vehicle mounted machinery
- DC rating eases integration into a wide variety of mobile equipment, including mobile cranes, vacuum trucks, stacker conveyors, trenchers, grinders, concrete mixers, pumpers, and pavers
- Allows the operator a wide range of movement, providing improved machine visibility and handling

Features and Benefits

- Most models weigh less than two pounds
- Slim-line pendant's lightweight design rests comfortably in the palm of your hand
- Ergonomic design offers comfortable control and performance with less effort and fatigue than traditional pendants
- Superior durability designed to survive even the most brutal environments, and the high-impact resistant, watertight enclosure is ideally suited for many applications
- 2, 4, 6, 8, 10 or 12 button configurations
- Suitable for AC or DC applications
- Switches are rated 2 Amp, 24 VDC, and 3 Amp, 250 VAC
- 1, 2 or 3 speed operation
- Impact resistant pendant enclosure is double insulated, chemically resistant and rated NEMA 1, 3, 4, 4X and 12
- Cable grip clamps provide a watertight sealed connection between cable and enclosure
- Switches are protected from internal/external contaminants
- Common circuit is pre-wired on all switches to simplify wiring
- Mechanical interlocks on single- and two-speed switches for enhanced safety
- Cumulative contacts on two-and three-speed switches provide precise detent feel
- Easy-to-read button functions
- Operating temperature range: -10°F to 150°F
- UL listed, CSA approved



