Product Name FLATTENING ADDITIVE

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

A matting powder for OceanMaster Topcoat Polygloss series. This product varies the degree of gloss without reducing the mechanical properties. Ideal to use when a lower gloss level is desired.

DIRECTIONS FOR USE

Usage

Add to any OceanMaster Polygloss 2 pack topcoat colours. Designed for spray application. Brush application may result in an uneven or semi gloss finish,

Coverage Refer to Polygloss Topcoat colours finish TDS

Mixing Ratio (Paint: Matting Powder) Matte Finish Spray: Mix 1:1 Eggshell Finish Spray: Mix 1: ¾ SemiGloss Finish Spray: Mix 1: ½

Thinner Ratio

Spray 15-20%

Pack Sizes 1KG / 5KG

PRODUCT INFORMATION

Finish : Matte, Eggshell, Semi- Gloss

QUICK TIPS

Product designed for spray application

Key to ensuring a good job is to Ensure proper surface preparation on various substrates before coating.

Use T300 thinner if necessary to degrease or wipe down surface prior to product application

Health and Safety

Provide adequate ventilation during use. Avoid contact with skin and eyes. Avoid breathing dust vapour or spray. Wear eye protection and gloves during use.

Always wash up with warm, soapy water after contact with skin.

RECOMMENDED SPRAY GUN SETUP BINKS

FLUID NOZZLE: 63-BSS 45-6321 (1.2MM) FLUID NEEDLE: 563A 47-56310 AIR NOZZLE 63-P 46-6000 Wet Film Thickness: 85 Microns Dry Film Thickness: 40 Microns





