Product information

Marine Fuel System Cleaner



Description

Highly effective combination of cleaning and preserving additives for 2-stroke and 4-stroke gasoline engines. Removes deposits on injection valves, intake valves, spark plugs and in the combustion chamber and prevents new deposits from forming. For a smoother running engine Eliminates starting problems and rough engine running. Preserves and protects the entire fuel system against wear, deposits and corrosion. Clean engines use less fuel and emit fewer pollutants.

MARINE BENZÍN SYSTEM REINIGE PROPORTO PROPORTO REINIGE REINIGE

Properties

- removes deposits from entire fuel system
- removes carbon deposits from intake valves and combustion chamber
- cleans the injection system
- saves fuel and reduces pollutant emissions

Technical data

Base additives, special liquid carrier

Color / appearance light yellow, clear

Form liquid

Odor characteristic

Density at 15 °C 0,82 g/ml

Flash point >63 °C

Viscosity at 40 °C <7 mm²/s

Areas of application

For all types of gasoline injection systems and carburetors. For adding to fuel tanks to deal with and prevent problems.

Application

500 ml is sufficient for 250 l of fuel. Filling the dosage chamber (25 ml) once is sufficient for 12.5 l of fuel.

Available pack sizes

500 ml Can sheet metal 25011

GB-DK-N-FIN-S-RUS

500 ml Can sheet metal 25010

D-F-I-E-GR

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de