Product information

Marine 4T Motor Oil 15W-40



Description

High-performance motor oil based on selected base oils and modern additive technology, developed specially for the maritime requirements. Even in extreme conditions guarantees optimum lubrication and reliable protection against wear. The high proportion of corrosion inhibitor guarantees protection against rust and corrosion.

Technical data

Total base number 10,5 mg KOH/g DIN ISO 3771

Sulfate ash 1,0 - 1,6 g/100g DIN 51575

Color number (ASTM) L 4,5

DIN ISO 2049

Properties

- high wear resistance

- tested for turbochargers and catalytic converters

- low evaporation loss

- high shear stability

can be used in gasoline and diesel engines with and without turbocharger

Approvals

ACEA A3 • ACEA B4 • ACEA E7 • API CI-4 • API SL • Mack E0-N • MAN M 3275-1 • MTU Typ 2 • Renault Trucks RLD-2 • Volvo VDS-3

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar ECF-1-a • Caterpillar ECF-2 • Cummins CES 20076 • Cummins CES 20077 • Cummins CES 20078 • Detroit Diesel • Deutz DQC III-10

Technical data

SAE class (engine oils) 15W-40

SAE J300

Density at 15 °C 0,875 g/cm³

DIN 51757

Viscosity at 40 °C 95 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 14 mm²/s

ASTM D 7042-04

Viscosity at -25 °C (MRV) < 60000 mPas

ASTM D4684

Viscosity at -20 °C (CCS) <= 7000 mPas

ASTM D5293

Viscosity index 150

DIN ISO 2909

HTHS at 150°C >= 3,7 mPas

ASTM D5481

Pour point -36 °C

DIN ISO 3016

Evaporation loss (Noack) 9 %

CEC-L-40-A-93

Flash point 230 °C

DIN ISO 2592

Areas of application

All-season oil for gasoline and diesel marine engines. Can be mixed with all commercially available motor oils.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed!

Available pack sizes

1 l Canister plastic 25015

D-BOOKLET

5 l Canister plastic 25016

D-BOOKLET

20 l Canister plastic 25061

D-GB

60 l Drum sheet metal 25017

D-GB

205 l Drum sheet metal 25018

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.