

SaveAqua info@saveaqua.com		Datasheet	Rev. 5
Hose Adapter (Adapter 2)		Model A	
Operating Temperature	0 to 40 °C	32 to 100 °F	
Storage Temperature	-10 to 40 °C	15 to 100 °F	
Operating Pressure	0 to 10 kPa	0 to 1.5 psi	
Operating fluid	water, potable water, filtered water. Water may contain standard amounts of disinfectant.		
Maximum WCH (water column height) above the tap during operation	1 m	40 in.	
Flow Rate ^{1, 2, 3}	6 litres per minute @ 60 cm of WCH	1.6 gallons (US) per minute @ 24 in. of WCH	
	2.4 litres per minute @ 10 cm of WCH	0.6 gallons (US) per minute @ 4 in. of WCH	
Materials ⁴	ABS.		
Weight ¹	4 grams	0.15 ounce (US)	
Connecting Thread	5/8 in.-18 TPI		
Out of Vertical Installation Angle ^{1, 3} (maximum)	15°		
Overall Dimensions ¹ (maximum)	5 cm long, 1.9 cm diameter	2 in. long, 3/4 in. diameter	
Compatibility	compatible with SaveAqua Tap Model A ⁵ . Flexible hose/tube with 1.3 cm (1/2 in.) inside diameter.		
Recyclable	Check with your nearest recycling facility. Plastic parts can be recycled as code No. 9 or ABS or No. 7.		
¹ Approximate values. ² At approximately 20 °C (68 °F) water temperature. ³ Values provided with SaveAqua Tap Model A installed. ⁴ All parts are manufactured from FDA grade materials after May of 2016. ⁵ Refer to Installation and Maintenance Instructions.			



Figure 1: Spigot Adapter