

Blend

A beautiful union of cement and fabric create a unique tile with the warmth of textiles and the strength of concrete.

1. 6 Colors
2. Matte finish
3. 12" x 24"
4. Mosaics and trim available



500-101



500-102



500-103



500-104




500-105




500-106

Sizes, Mosaics and Trims




12x24



2x2 Mosaics
Sheet Size: 12x12



2x6 Interlocking Mosaics
Sheet Size: 12x14



Bullnose
3x12





Floor and Wall Solutions

Order Samples at
331-702-2178

www.mondanicollection.com

1. FINISHES:

Matte

Thickness: 8 mm

Recommended Grout Joint: 3/32" or greater

All sizes modular with 3/16" grout joint

Grout joints of 1/8" inch or less, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

2. TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	Mondani Results
Water Absorption	C373	Impervious <0.5%	Pass
Bond Strength	C482	≥ 50 psi	200 psi
Breaking Strength	C648	≥ 250 lbf	≥ 400 lbf
Hardness (Mohs)	(No regulated)	Range 0 - 10	6
Frost Resistance	Scratch Test	No sample must show alterations to surface	
(Freeze/Thaw)	C1026	No Requirement	Pass
Chemical Resistance	C650	Range E - A	Unaffected
Coefficient of Friction (Dynamic)	DCOF Acutest m (wet)	≥ 0.42*	> 0.42
Aesthetic Classification	Visual Evaluation Shade & Texture	No Requirement Range V0 - V4	V2

* All values given are for matte and semi-polished. No values are given for polished material. Mondani Collection does not recommend polished surfaces in area subject to exposure from grease, oil or water.

For level interior spaces to be walked upon when wet (see ANSI A137.1 section 6.2.2.1.10 – Section 9.6 for test procedure).

3. INSTALLATION

All installation work using Mondani Collection tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

Installation or setting materials:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4. and TCNA Details EJ171.

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.





Floor and Wall Solutions

Order Samples at
331-702-2178
www.mondanicollection.com

