


## Caprice

Caprice Is a contemporary veined stone look reminiscent of travertine with a quartzite twist. Caprice's soft tones and subtle movement will elevate your projects design style.

1. 4 Colors
2. Rectified 12" x 24" and 6" x 24"
3. Matte Finish
4. Decos and Cove Base available



**400-601**



**400-602**



**400-603**



**400-604**

### Sizes, Mosaics and Trims



**12x24**



**6x24**



**2x2 mosaic**  
Sheet Size: 12x12



**Bullnose**  
3x24



**Cove Base**  
6x12

### 1. FINISHES:

Matte

**Thickness: 9 mm**

**Recommended Grout Joint: 3/32" or greater**

**All sizes modular with 3/16" grout joint**

**Grout joints of 1/8" inch or less, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.**

### 2. TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	Mondani Results
Water Absorption	C373	Impervious <0.5%	Pass
Bond Strength	C482	≥ 50 psi	200 psi
Breaking Strength	C648	≥ 250 lbf	> 250 lbf
Hardness (Mohs)	(No regulated)	Range 0 - 10	6
Frost Resistance		No sample must show alterations to surface	Pass
(Freeze/Thaw)	C1026	No Requirement	
Chemical Resistance	C650	Range E - A	Unaffected
Coefficient of Friction (Dynamic)	DCOF Acutest m (wet)	≥ 0.42*	> 0.42
Aesthetic Classification	Visual Evaluation Shade & Texture	No Requirement	
		Range V0 - V4	V2

\* All values given are for matte and semi-polished. No values are given for polished material. Mondani Collection does not recommend polished surfaces in area subject to exposure from grease, oil or water.

For level interior spaces to be walked upon when wet (see ANSI A137.1 section 6.2.2.1.10 – Section 9.6 for test procedure).

### 3. INSTALLATION

All installation work using Mondani Collection tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

Installation or setting materials:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4. and TCNA Details EJ171.

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.



