


ADA signage compliance tips.



Signs that require Braille and tactile lettering.

Signs designating permanent rooms and spaces that are not likely to change over time must comply with these standards. Braille and tactile lettering are required so they can be located and accessed by people who are functionally blind. Examples include restrooms, room names and numbers, and floor numbers.

- Minimum 1/32" raised tactile characters
- Must use all uppercase, sans serif text
- Uppercase letter "I" must measure between 5/8" - 2"
- Must meet font requirements (see below)
- Must contain Contracted Braille (formerly Grade 2 Braille) with domed or rounded shape Braille dots positioned under the corresponding text
- Braille must be separated by at least 3/8" from any tactile character and at least 3/8" from raised border or decorative graphic
- If pictograms are used, they must be in a field measuring 6" high and accompanied by tactile and Braille lettering below the field
- Text cannot be incorporated into pictograms
- Characters and backgrounds must have a non-glare finish
- Characters must contrast with their background (either light color characters on a dark color background, or dark color characters on a light color background)



Font requirements. The ADAAG indicates specific requirements for the stroke width and body width of the font you use on signs using tactile lettering. The stroke width of the uppercase letter "I" cannot be less than 15% of the height of the character. And the body width of the uppercase letter "O" is to be between 55% and 110% of the height of the uppercase letter "I".

Mounting requirements. The ADAAG indicates specific requirements for the mounting height of signs that require tactile lettering. The minimum height a sign is to be mounted, measured from the floor to the baseline of the lowest tactile character, is 48". The maximum height a sign is to be mounted, measured from the floor to the baseline of the highest tactile character, is 60".

Clear space requirements. Signs with tactile lettering are to be located in a position with a minimum 18" x 18" clear floor space (measured from the center of the tactile lettering on the sign). This clear floor space is to be beyond the arc of any door swing.

Signs that have dimensional requirements. Directional and informational signs used in functional spaces and overhead signs do not require Braille and tactile lettering, but must have proper character proportion and height, finish and contrast.

- May use upper and lowercase, or a combination of both
- Font may be serif, simple serif or sanserif, but must not be italic, oblique, script or highly decorative
- Do not condense or extend typefaces
- The size of the lettering is dependent on the distance the sign reader is expected to be from the sign
- Must meet font requirements (previous)
- Characters and backgrounds must have a non-glare finish
- Characters must contrast with their background (either light color characters on a dark color background, or dark color characters on a light color background)


Signs with no requirements. Signs used for building directories, menus, seat and row designations in assembly areas, building names and address, and company names or logos are not required to comply with the guidelines.

Available in-stock, nationwide.

Gemini is committed to providing you with the best engraving materials. The best value. And the best service. That's why we've partnered with the best providers across the country to stock and distribute Duets right near you. Contact your engraving materials partner for the fastest availability of the comprehensive and growing selection of Duets substrates, with the familiar personal and local service you're accustomed to receiving.

We've got you covered.

If you have technical questions about Duets substrates, need swatch chips, samples or require assistance, our entire team at Gemini and our partners are ready to assist you. Go to DuetsByGemini.com or call 800.548.3356



Find a Duets partner near you at:
DuetsByGemini.com/partners

For more information call 800.548.3356

Information herein is intended as a summary of the ADA law as it pertains to signage, and is solely intended as a reference for our customers. Gemini Incorporated and its partners assume no liability for errors resulting from the use of, or the interpretation of, this material. Some local and state building code requirements may be more stringent than the federal law.

©2016 Gemini Incorporated. Duets™ is a trademark of Gemini, Inc. Printed in USA.



DuetsTactiles™ ADA Color & Contrast Guide



Substrates for superior ADA signage.

A better sign starts with better materials.

ADA wayfinding signage is a vital component to any architectural sign-making business. Your customers rely on you not only produce appealing signage that enhances the interior space of a building, but also complies with the Americans with Disabilities Act Accessibility Guidelines (ADAAG).

DuetsTactiles™ by Gemini offers a wide selection of high-performance substrates designed specifically for ADA wayfinding appliqué signage.

Color contrast made simple.

The ADAAG provides guidance on surfaces that need to contrast visually with their surroundings to assist the disabled, including those who are visually impaired. Requirements for ADA wayfinding state that signs must be non-glare and characters must contrast with their background.

The chart on the inside of this guide compares all of the possible color combinations that can be achieved with DuetsTactiles substrates and appliqué. Choose the color schemes that are compatible with building décor, and the color combination that provides a significant degree of contrast between characters and background, giving consideration to lighting and environmental factors.



DuetsTactiles™ P/N & COLOR GUIDE

1/32" A* 1/32 1/16 1/8										
CMYK RGB PMS	0-0-0-0 255-255-255 Trans. White	0-0-0 255-255-255 Trans. White	3-0-1-0 240-247-251 7541	0-0-0-0 248-248-248 Cool Gray 1	0-1-4-0 255-251-242 Warm Gray 1	0-11-100-0 255-219-0 108	0-29-73-25 198-149-73 4645	0-60-100-0 245-130-32 166	0-58-83-40 162-88-38 1615	0-87-80-42 155-42-34 484
1/32" A* 1/32 1/16 1/8										
CMYK RGB PMS	0-100-90-23 190-19-35 1797	0-92-52-75 94-0-23 216	0-63-21-50 143-73-89 7637	0-81-22-11 216-79-121 213	97-40-6-0 0-125-197 298	49-15-0-6 116-172-214 284	19-4-0-66 93-106-117 5415	100-50-0-39 0-76-130 300	100-70-0-56 0-42-95 662	79-63-0-70 21-35-78 7694
1/32" A* 1/32 1/16 1/8										
CMYK RGB PMS	69-32-0-78 12-50-79 7463	36-0-28-68 69-97-89 5487	68-0-25-45 20-122-127 7474	83-0-33-47 0-113-116 7475	46-0-49-12 125-183-142 346	94-0-94-3 0-164-84 7724	100-0-72-53 0-98-70 342	0-8-20-4 243-224-196 Warm Gray 1	0-2-16-7 239-231-206 Warm Gray 1	0-4-24-5 L-010-313-A 21-35-78 Warm Gray 1
1/32" A* 1/32 1/16 1/8										
CMYK RGB PMS	0-6-23-23 205-192-164 7734	0-11-35-1 251-222-172 7401	0-13-43-16 218-190-137 453	26-23-33-0 191-184-168 452	0-15-35-38 173-150-119 8021	0-17-29-67 134-115-98 Warm Gray 7	0-46-85-66 114-69-13 161	0-48-55-67 112-67-47 7518	0-41-35-93 50-26-21 439	1-0-9-11 225-226-212 Cool Gray 2
1/32" A* 1/32 1/16 1/8										
CMYK RGB PMS	2-0-2-40 163-167-167 Cool Gray 7	8-0-13-20 194-203-190 Warm Gray 3	0-3-16-58 134-129-117 Cool Gray 9	0-10-7-74 100-91-91 432	0-7-19-83 78-75-73 Black 7	0-3-7-84 78-75-73 Black 7	29-14-0-100 0-0-0 Black			

NOTE: Colors portrayed and/or color formulas expressed herein are for reference only. Duets materials are tightly controlled for color consistency during manufacturing, but the colors in printed, electronic or online representations may vary from actual material colors. We recommend requesting a free color chip or referring to the Duets color swatch chip binder to validate material colors.

DuetsTactiles™ ADA & APPLIQUÉ CONTRAST GUIDE

	APPLIQUÉ SUBSTRATE																																													
	Black	Graphite	Denim Blue	Chocolate Brown	Majestic Blue	Cobalt Blue	Charcoal Grey	Chestnut	Burgundy	Merlot	Evergreen	Frosted Plum	Blue	Medieval Copper	Aged Bronze	Red	Pipstone	Intense Teal	Lagoon	Pink	Slate Blue	Spring Green	Spruce	Taupe	Orange	Mint	River Clay	Periwinkle	Light Blue	Gold	Putty	Latte	Desert Sand	Khaki	Silver	Oyster Shell	Yellow	Light Grey	Bone	French Vanilla	Almond	Bisque	Warm White	White	Frost	Bright White
Clear/Matte*																																														
Bright White																																														
Frost																																														
White																																														
Warm White																																														
Bisque																																														
Almond																																														
French Vanilla																																														
Bone																																														
Light Grey																																														
Yellow																																														
Oyster Shell																																														
Silver																																														
Khaki																																														
Desert Sand																																														
Latte																																														