DE-ICER

REMOVES ICE & FROST

PCLAR RENOVATE A REVIVE A PROTECT

PERFORMANCE ADVANTAGES

- Prevents re-freezing
- Fast and effective
- Instant melting of ice and frost
- Does not affect automotive paintwork
- Works down to -4°F



HOW TO VIDEO

View our handy 'how-to' video to understand how to get the best results from our products.



Multi Surface Use



Melts Ice Fast



To Use



DIRECTIONS



Step One

Remove all loosely adhering ice, snow, sleet, slush etc. with a scraper or similar.



Step Two

Shake can thoroughly before use and apply directly to the area from a distance of 12 inches.



TECHNICAL DATA SHEET

DE-ICER



USES

- On all hard, impervious surfaces including windshield, side and rear screens, mirrors, gates etc.
- Suitable for defrosting locks, hinges and other mechanisms affected by the effects of ice.

COLOR RANGE

CLEAR

PACK SIZE

17oz.

DRYING TIME

- No loss of application pressure under cold conditions of use.
- Instant melting of ice and frost.
- Inclusion of ammonia provides good detergent properties.
- Suitable for use at temperatures down to -4°F.
- Contains additives to help prevent re-freezing.
- Does not affect automotive paintwork.
- Does not affect windshield rubbers.

SHELF LIFE

Keeps for up to 2 years when stored correctly.

PREPARATION AND APPLICATION

- Remove all loosely adhering ice, snow, sleet, slush etc. with a scraper or similar.
- Shake can thoroughly before use and apply directly to the area from a distance of 12 inches.
- Allow the ice to melt and dry the surface with a cloth.
- Repeat if required.

PRECAUTIONS

- Flammable keep away from sources of ignition.
- Ensure good ventilation during application use outdoors or in a well ventilated area.
- Wear gloves, goggles and suitable protective clothing.
- In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Remove contact lenses if present and easy to do.
- Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.

- Keep out of reach of children.
- May cause drowsiness or dizziness.
- Avoid breathing vapour/spray.
- Dispose of contents/container in accordance with local regulations. Repeated exposure may cause skin dryness or cracking.
- ▶ **CAUTION:** Pressurised container: May burst if heated. Protect from sunlight. Do not expose to temperatures exceeding 122°F. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Use only as directed.

TECHNICAL DATA SHEET

DF-ICFR



SAFETY

Good working practices should be followed.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Polar Specialist Coatings Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself. If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.

VIEW OUR FULL RANGE OF PRODUCTS www.polarcoatings.co.uk



Road 3, Winsford Industrial Estate, Winsford, Cheshire. CW7 3PD info@polarcoatings.co.uk | 0161 850 0379

Innovate Pioneers for Specialist Coatings

Polar provides you with the expertise and quality to transform & renovate all your DIY projects.

Formerly the creators of Johnstone's paints with over 130 years manufacturing experience...

We deliver reliable, high-performance paints that revive, protect & maintain your home.

