



Excelon™ Vinyl Composition Tile

The durable construction of Excelon™ VCT ensures lasting beauty in high-traffic areas such as retail, education and housing spaces. The Excelon™ VCT harmonises with other products across the entire Armstrong Flooring™ portfolio to help you execute your design vision.

Key features:

- Economical
- Outstanding stability and durability
- Quick to install
- Easy to repair
- Flexible design opportunities

Product Classification

Type of floor covering	ISO 10595	Vinyl Composition Tile
Commercial classification	ISO 10874	33 
Light industrial classification	ISO 10874	42 

Physical Properties

Manufactured in	-	South Korea
Tile size	ISO 24342	300 x 300mm
Overall thickness	ISO 24346	3.0mm
m ² /carton	-	3.33m ²
Tiles/carton	-	37
Weight/carton	-	21kg
Carton/pallet	-	72
Dimensional stability	ISO 23999	Pass
Straightness/Squareness	ISO 24342	Pass

Fire & Slip Performance

Wet pendulum	AS 4586 (Appendix A)	P2
Critical radiant flux	ISO 9239-1	≥ 8kW/m ²
Smoke development rate	ISO 9239-1	≤ 750%. minutes

Installation

Installation to AS1884	Full stick with Armstrong PS-820 adhesive
------------------------	---

Applications



Supermarket



Residential



Retail



Education

Visit www.armstrongflooring.au or contact Customer Service on 1800 632 624 for technical data, installation, cleaning and maintenance instructions.