

**Product Classification**

Type of floor covering	EN/ISO 10582	Luxury Vinyl Plank
Classification	ISO 10874	Domestic Heavy Duty (23) Commercial Heavy Duty (33) Industrial General Duty (42)
Warranties*	Domestic Commercial - available upon request	25 years 15 years

\*All warranties are in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the residential warranty, please see [armstrongflooring.au](http://armstrongflooring.au) or contact our Head Office, or for the commercial warranty, contact your Armstrong Flooring Territory Sales Manager

**Product Structure**

Dimensions (mm)	1500 x 185 x 2.5mm
Surface treatment	PUR
Wear layer (mm)	0.55mm
Bevel	Yes
Installation	Glue down as per current Australian Standard AS1884

**Packaging**

Planks/carton	10
m2/carton	2.77
Kg/carton	12.3

**Sustainability**

TVOC Emissions	Compliant low emitting VOC emissions
Global GreenTag	GreenRate Level A

Product Testing		Standard	Requirement	Result
Slip	Wet pendulum	AS4586	-	P3
Fire	Critical radiant flux	AS ISO 9239-1	≥ 4.5kW/m2	9.7kW/m2
	Smoke development rate	AS ISO 9239-1	≤ 750%.minutes	87%.minutes
Acoustic	Impact sound insulation <small>(150mm concrete with 3mm underlay and drop ceiling)</small>	ISO 10140-3 ISO 717-2	≤ 62 dB	Ln,w = 43dB (5 star)
Surface	Abrasion	EN660-2	-	Group T
	Martindale (wear resistance)	EN16094	MSR-B2	MSR-B2
	UV adhesion		≥ 2	≥4B
	Colour fastness	ISO 105-B02	≥ 6	6
Core	Dimensional tolerance	EN427	Length ± 0.30mm Width ± 0.12mm	Length 0.02mm Width 0.07mm
	Peel strength	ISO 24345	> 50N	82.25N
	Dimensional stability/MD (80°C 6hr)	ISO 23999	≤   0.25%	0.14%
	Dimensional stability/AMD(80°C 6hr)	ISO 23999	≤   0.25%	0.08%
	Curling (80°C 6hr)	ISO 23999	≤   2   mm	0.3mm
	Residual indentation	ISO 24343	≤ 0.10mm	0.08mm