

ArmstrongFlooring™



Natural Creations™ XL
Luxury Vinyl Plank

Barnyard Grey | 3X168011

Natural Creations™ XL

Luxury Vinyl Plank

As functional as it is beautiful, the Natural Creations™ XL range features an array of exclusive timber colourways in wide format planks that are designed to complement any style interior. Thoughtfully designed for modern and contemporary spaces to offer a homely and comfortable feel all year round.

Features & Benefits

Natural Creations™ XL meets high performance criteria on a range of applications incorporating a high density interlayer and a protective PUR coating that delivers outstanding durability and protection. Natural Creations™ XL is scratch, scuff and slip resistant combined with a 100% waterproof surface^ for life's spills and inevitable mishaps.



Durable

Domestic Heavy Duty (23) and Commercial Heavy Duty (33) offering long term durability.



Low Maintenance

Easy to clean PUR coating for low maintenance and resistance to spills and scratches.



Pet Friendly

Scratch and stain resistant surface is ideal for household pets.^



Waterproof Surface

Not affected by spills, suitable for kitchens.^



Kid Friendly

Easy care and cleaning is suitable for young children.



Micro-Bevelled

Superior look and feel with a micro-bevelled edge.



Residential Warranty

25 year residential warranty*



Stain Resistant

PUR coating for improved stain resistance, ideal for kitchens.



^Subject to proper installation and care and maintenance as set out in the Armstrong Flooring Installation Instructions and Cleaning and Care Instructions.

*All warranties are in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the residential warranty, please see armstrongflooring.au or contact our Head Office. For the commercial warranty, contact your Armstrong Flooring Territory Sales Manager.



Natural Creations™ XL

Spotted Gum

A timeless design, Spotted Gum suits an array of interiors from contemporary to classic.



Natural Creations™ XL

Tasmanian Oak

A minimalist aesthetic designed for modern interiors, offering a sleek and unique sense of style.



Natural Creations™ XL

1500 x 230 x 5.0 mm



Blackbutt | 3X388901



Tasmanian Oak | 3X388801



Valley Oak - Haze | 3X109508



Riverland - Smoke | 3X111906



Spotted Gum | 3X389001



Valley Oak - Mist | 3X109505



Riverland - Limed | 3X111907



Riverland - Ash | 3X111903

Natural Creations™ XL

1500 x 230 x 5.0 mm



Oak - Tranquil | 3X057014



Oak - Harmony | 3X057015



Barnyard Grey | 3X168011



Barnwood - Ombre | 3X102605

Colour swatches may vary between digital brochure to real life product and are to be used as a guide only - refer to our [Colour Variation Factsheet](#). It is recommended you view the actual product in store - visit our [Store Locator](#).



Natural Creations™ XL

Oak Tranquil

A rich and warming colourway, Oak Tranquil provides character to any space.

Oak Tranquil | 3X057014

Product Specifications

Product Classification

Type of floor covering	EN ISO 10582	Luxury Vinyl Plank
Classification	ISO 10874	Domestic Heavy Duty (23)
		Commercial Heavy Duty (33)
		Industrial General Duty (42)
Warranties*	Residential	25 Years
	Commercial available on request	15 Years

*All warranties are in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the residential warranty, please see armstrongflooring.au or contact our Head Office, or for the commercial warranty, contact your Armstrong Flooring Territory Sales Manager


Product Structure

Dimensions	1500 x 230 x 5mm
Surface treatment	PUR
Wear layer (mm)	0.55 mm
Core	Double fibreglass reinforced
Bevel	Micro
Installation	Glue down as per current Australian Standard AS1884

Packaging

Planks/carton	6
m ² /carton	2.07
Kg/carton	19.2

Product Structure



Product Testing

		Standard	Requirement	Result
Slip	Wet Pendulum	AS4586	-	P3
Fire	Critical radiant flux	AS ISO 9239-1	≥ 4.5kW/m ²	8.6kW/m ²
	Smoke development rate	AS ISO 9239-1	≤ 750%.minutes	180%.minutes
Acoustic	Impact sound insulation <small>(150mm concrete with 3mm underlay and drop ceiling)</small>	ISO 10140-3 ISO 717-2	≤ 62dB	Ln,w = 42dB (5 Star)
	Impact insulation class <small>(150mm concrete with 3mm underlay and drop ceiling)</small>	ASTME989-21	-	IIC = 67
Surface	Abrasion	EN660-2	-	Group T
	Martindale (wear resistance)	EN16094	MSR-B2	MSR-B2
	UV adhesion		≥ 2	≥ 4B
	Colour fastness	ISO 105-B02	≥ 6	6
Core	Dimensional tolerance	EN427	Length ± 0.30mm	Length 0.1mm
		-	Width ± 0.12mm	Width 0.09mm
	Peel strength	ISO 24345	≥ 50N	119.10N
	Dimensional stability/MD (80°C 6hr)	ISO 23999	≤ 0.25%	0.04%
	Dimensional stability/AMD(80°C 6hr)	ISO 23999	≤ 0.25%	0.03%
	Curling (80°C 6hr)	ISO 23999	≤ 2 mm	-0.5mm
	Residual indentation	ISO 24343	≤ 0.10 mm	0.09mm

Sustainability


Global GreenTag GreenRate Level A

Collection



View Flooring in My Space

www.armstrongflooring.au/naturalcreationsxl



ArmstrongFlooring™

29-39 Mills Road, Braeside VIC 3195

1800 632 624

customerservices@armstrongflooring.au

www.armstrongflooring.au