

# **Glass Cutting Board/Cheese Board Transferring Instructions**

Read These Instructions COMPLETELY before you begin.

# Supplies Needed

- Glass Cutting Board or Cheese Board
- Black Wire Frame (optional)
- Heat Resistant Felt Pad
- Oven mitt or heat-resistant gloves (for removing product from heat press)

# Step 1: Adjust Heat Press

Heat Press Temperature:	400° F
Dwell Time:	3 <sup>1</sup> / <sub>2</sub> to 5 minutes
Pressure:	Firm

**Note**: These instructions, including transfer times and temperatures, are based on the inks, paper, presses, and products we use. Your inks, papers, etc. may require adjustments in your time/temp settings.

# Step 2: Design Your Transfer

Design your sublimation transfer so that the image is **<u>right-reading</u>**, not mirrored.

#### Step 3: Transfer the Image

- 1. Place the Heat Resistant Felt Pad on your heat press platen.
- 2. Place your transfer, face-up, on the Felt Pad.
- 3. Place the Glass Cutting Board or Cheese Board, white coated side down, on the transfer.
- 4. Using **Firm** pressure, press at **400° F** for **3**<sup>1</sup>/<sub>2</sub> **to 5 minutes**.

#### Step 4: Set into Wire Frame (optional)

You can set the Glass Cutting Board into the optional black wire frame using 100% silicone aquarium sealant, available at most hardware stores. Follow glue instructions provided with the product you use.

#### Transfer Tips, Techniques & Troubleshooting

Although the glass cutting boards are dishwasher safe, as with any custom-made product, we recommend hand-washing.

# **Transfer Tips**

- 1. What you see is what you get. If immediately upon opening the press you find the color development to be weak, close the press immediately for another 30 seconds and check again. Continue until you find the ideal dwell time for your press.
- 2. Package glass cutting boards with matching or complementary plates, coasters, mugs, glass steins, placemats, napkins, or other table accessories.
- 3. Display glass cutting boards on stands to catch the attention of your customers.
- 4. When gluing these tiles into wood or metal frames we recommend 100% silicone aquarium sealant.

# **Customer Support**

For questions regarding this, or any of our products, call our **customer support** line toll-free at **877.795.1500**. You may also write to us at <u>support@laserreproductions.com</u>.