



VITILAN EBIKE

Operation and maintenance manual

 www.vitilanebike.com



TABLE OF CONTENTS

Importance..... P1

Models and Pictures..... P2

Specifications P3

Safety and Compliance with the Law P4

Assembling Your New e-Bike..... P5-P9

Operating Your New e-Bike P10-P12

Intelligent Liquid Crystal Instrument..... P13-P30

Safety P31-P32

Trouble Shooting P33

PLEASE NOTE:

This manual is not intended as a detailed user, service, repair or maintenance manual. Please seek assistance from a qualified technician for service, repairs or maintenance.

IMPORTANCE

When using the electric bicycle, basic safety precautions should always be followed, including the following:

1. Read all instructions.
2. To protect against fire, electric shock and injury to persons, do not immerse cord, plugs, or e-bike in water or other liquid.
3. Close supervision is necessary when the e-bike is used by or near children.
4. Unplug from outlet when not in charging and before cleaning.
5. Do not operate the e-bike with a damaged cord or plug or after the e-bike malfunctions, or has been damaged in any manner. Take the e-bike to the nearest authorized service bike shop for examination, repair or adjustment.
6. The use of accessory attachments not recommended by the e-bike manufacturer may result in fire, electric shock or injury to persons.
7. Do waterproof when using on a rainy or snowy day.
8. Do not let cord hang over the edge of table or counter, or touch hot surfaces.
9. Do not place on or near a hot gas or electric burner, or a heated oven.
10. Always attach the plug to the battery first, then plug the cord into the wall outlet.
11. Do not use the bike for other than intended use.
12. Save these instructions.

***Note that this is a general manual. VITILAN reserves the right to make changes to products and designs. The e-bike you own may not be the same style as the pictures shown in this manual.**

MODEL: U7



Specifications

- MODEL: **U7 2.0**
- Frame Construction: Aluminum Alloy
- Gear Range: 7-speed type
- Tire Size: 20" (565mm)
- Climb Grade: 30 degree
- Max load: 150kg (330 lbs)
- Max Speed: 28mph(Actual speed depends on road conditions, weather, rider weight)
- Power: 750W
- Battery Capacity: SAMSUNG 48V 20Ah
- Battery Charger: US Standard 54.6V 3.0A Charger, Voltage 110-240V
- Battery Operational Temperature: 0°to 40° Celsius (32°to 104°Fahrenheit)
- Battery Life: Approximately 500-800 complete charge/discharge cycles
- Folding risers: There is a toothed folding riser, right fold, 8 degrees forward
- Seat tube: 25.4*350MM aluminum alloy flip shock absorbing seatpost
- Sprocket: 3/32/48T*170mm, STEEL, sand black, square hole inch, with 9/16, aluminum alloy double chain cover

Read This First: Safety and Compliance with the Law

Congratulations on your purchasing of your new e-bike. Your new e-bike is an excellent piece of personal transportation equipment that will give you good service for many years.

Before you start using your e-bike, we want you to be aware of a few important points. Please read this section carefully.

- **Observe Laws Regarding the Use of Battery-Operated Bicycles**

Your e-bike is designed and manufactured to meet safety requirements as a battery-operated bicycle. However, state and local laws governing the use of battery-operated bicycles on public roadways, parks, and other open areas may differ. Please check with your local authority before using your e-bike in public areas.

- **Observe Laws Regarding the Use of Bicycles**

Note that all laws regarding the use of bicycles in public areas, such as those mandating the use of helmets and the use of infant seats, will automatically apply for e-bikes. Check with your local authority on what restrictions might apply.

- **The Lithium-ion Battery of Your e-Bike**

Your e-bike is equipped with the latest battery technology. The lithium-ion battery is much lighter than lead- or nickel-based batteries that are being used in some older models.

- **Your First Ride**

Please be VERY CAREFUL when you are ready to get on your e-bike for the first time because that the e-bike moves significantly faster than a regular bicycle at active power-assisted mode. Take your e-bike to an area with a lot of open space before you start. Do not start pedaling hard as soon as you get on the e-bike (as you normally would be with a regular bicycle), as the e-bike will accelerate under pedal-assist mode and you may be unprepared for the sudden increase in speed. However, after a few times, you will enjoy using the pedal-assisted function.

Assembling Your New e-Bike

If you purchased your e-bike unassembled, please follow these instructions to assemble your e-bike under the guidance of an adult or a qualified technician. Assembly is quite easy as most of the parts are already assembled; you need only to put a few pieces together to complete the job.

For more information. Please refer to the following way:

Email: support@vitilanebike.com

Facebook: Vitilanebike


Instagram: Vitilanebike

Website: www.vitilanebike.com


Youtube: Vitilanebike

Twitter: Vitilanebike


Remove the Battery



1. Open the buckle.



2. Push the key up once, then turn the key to retract the lock.



3. Fold the frame and remove the battery.



● Check that the Package is Complete and Undamaged

Your e-bike comes in a carton containing the following:

- ✧ The main body of the e-bike – consisting of the frame, the front and rear wheel, the gear and chain, the front and rear brake, the battery on the frame, the rear fender.

- ✧ The handlebar subassembly with the battery's keys that attached on it – the handlebar subassembly is not really separate, as it is connected to the main body by the brake cables and electrical wires. The handlebar also has the brake levers and gear control already assembled. Additionally, the handle also has an integrated control for the throttle mode power-assisted, a display panel.


- ✧ The Seat – the seat is attached to its pedestal stem.

- ✧ Tools and other parts –tools, one charger, a pair of foot pedals and this manual, they are contained in a separate box.

- ✧ Before the bike leaves the factory, the tire pressure is about half as low. Before riding, check for adequate air pressure.

- **Assembly - Step 1: Attach the handlebar subassembly**

Stand the main body of the e-bike on the kickstand. Stand up and lock the steering column that is at the front of the main body frame, insert the stem of the handlebar subassembly into it. Make sure that the fork (that will hold the front wheel) is pointing forward, and orient the handlebar accordingly. Insert the stem all the way and tighten from the top using the quick lock.



- **Assembly - Step 2: Installing the Seat and Pedals**

Insert the pedestal stem of the seat into the seat column of the main body frame, use the built-in lever to tighten.

Attach a pedal on each side of the crank, note the distinction between left pedal and right pedal, tighten with the multi-tools.

Note the distinction: the installation of the left and right pedals



Inflate the tires to proper pressure.

At this point, your e-bike is a completely functional bicycle, although without any battery operated to function as yet. Check all tightening points to make sure. Take a short ride. Adjust the height of the handlebar, and the height and the tilt of the seat, if necessary, for maximum comfort.

- **Assembly - Step 3: Charging the Battery**

Take out the charger from the box, attached the power cord and insert that to any wall outlet. Insert the plug at the end of the smaller cable into the charging terminal of the battery and start charging. The charging terminal is on the side of the battery opposite to a hole on the side of the frame. The LED on the charger glows RED while charging and glows GREEN when charging is complete. The battery should be turned OFF while being charged. When the LED on the charger turns Green, disconnect the charging cord and cover the charging terminal with the rubber cap. If a battery is installed on the e-bike and turned ON, the display panel will show the charge level of the battery when the bike turned ON.

You are now ready to start using your e-bike.

Operating Your New e-Bike

The method to turn on the bike is:

- I. Turn the battery lock clockwise to the bottom to open the battery;
- II. Press power button on the left handle bar until the display lights on;
- III. Ride on the bike and twist the throttle bar or pedal the bike, the bike will move, you can change the power level with control buttons, level 1 is the slowest and level 5 is the fastest, level 0 is human model.

Your e-bike is driven by a motor embedded in the hub of the rear wheel. The motor is powered by a battery. The amount of power delivered to the motor, and hence the accelerating force on the e-bike, is controlled by you in a way according to the power-assisted mode or full power mode you choose.

You can configure the e-bike to operate in the pedal-assist-only-mode or the full power mode (should check against local laws to ensure full power mode is permitted) where you can also use the hand throttle to deliver power to the motor.

● Your First Ride

(Reprinted from the Safety and Compliance with the Law section)

Please be VERY CAREFUL when you are ready to get on your e-bike for the first time because the e-bike moves significantly faster than a regular bicycle at active power-assisted mode. Take your e-bike to an area with a lot of open space before you start. Do not start pedaling hard as soon as you get on the e-bike (as you normally would do with a regular bicycle), as the e-bike will accelerate under pedal-assist mode and you may be unprepared for the sudden increase in speed. However, after a few times, you will enjoy using the pedal-assisted function.

● Pedal-Assisted

You must turn on the battery to use the e-bike in pedal-assisted mode.

In the pedal-assisted mode, power assist is triggered when you pedal forward, and power assist stops when you stop pedaling, sometime would be delay. In other words, power assist happens as long as you pedal. You don't need to pedal hard. All you need is to apply a light force to the pedals continuously to maintain the current flow. When you apply one of the brakes, power assist will automatically stop, allowing the e-bike to slow down and stop. Power assist will turn itself off when the e-bike has reached the maximum speed that the power level you choose.

You should use the gear shifter at the handlebar to set the gears appropriately according to road conditions and pedal, as usual, you will find that you need to exert a lot less effort and the e-bike travels faster and at a more steady speed.

- **Cruise Control**

Cruise Control will be triggered when you holding throttle for 8 seconds, and it will be released by braking/pedaling or throttling.

- **Thumb throttle Control**

In the hand throttle mode, amount of power assist is determined by the throttle switch controlled by your hand. You control the throttle by twisting it from its resting position, the farther the throttle switch is from its resting position, the more power is delivered to the motor to accelerate the e-bike. When you want to slow down, you simply release the throttle and let it return to its resting position, and simultaneously apply the brakes if necessary.

You do not need to pedal the e-bike if you use the hand throttle. However, you can pedal while commanding power assist. If you do pedal to help the movement, you conserve energy and the charge in the battery will last longer.

- **Charging Your e-Bike Battery**

Your e-bike battery is a lithium-ion battery. Lithium-ion battery requires specially designed chargers. You should never charge your battery with a substitute charger that is not designed for this use. Use of an unsuitable charger to charge a lithium-ion battery will result in overheating, fire or even explosion. Ensure charger voltage is consistent with battery voltage. If your charger is lost or damaged, contact your dealer to order a replacement.

Charge your battery while the e-bike is not in use. You should turn off the battery before you charge it. You may charge your battery while it is mounted on the e-bike, or after it has been removed from the e-bike.

Do not place either the charger or the battery near flammable substances while charging is taking place. Charging should not be done in the vicinity of infants and small children. It is also prudent to remove valuable objects from the immediate vicinity of the battery while it is being charged. Don't charge in unattended condition for a long time. For the safety of you and your family, it is recommended not to charge in the middle of the night.

In order to maintain battery life, do not charge until the battery completely discharged, it is recommended to start charging when the power is less than 20 percent. If the battery will not be used for an extended period of time, charge it fully and recharge it every month. If not used for several months, the battery may be completely self-discharge and unable to charge.

The length of charging time depends on the level of charge the battery still holds. If a battery is completely discharged, it will take about 6 hours to be fully recharged. When a battery is fully charged, the LED on the charger will transition from RED to GREEN. At this point, you should disconnect the charger. Do not leave the charger

connected to the battery for a very long period of time after charging is complete.
(Leaving it connected for an overnight charging is OK.)

It is normal for the charger and the battery to be slightly hot while charging is on-going.

● **Removing the Battery from the e-Bike**

The battery is an important and costly part of the e-bike. It is designed to be locked into position with a key to preventing theft. You can take further precaution by removing the battery while the e-bike is parked unattended. You may also have a need to remove the battery from the e-bike to recharge it at a location where you cannot park your e-bike.

The method to remove the battery is:

- I. Open the cap of the charging port and fold the bike;
- II. Insert the key into the battery, hold pressing the key a bit until twist clockwise to the end (Note: You can't remove the battery until the lock bar withdraws into the battery completely);
- III. Slip off the battery, the battery is quite heavy and you should take care not to drop it.

● **Maximizing the Riding Range**

Many factors affect the rate of use of the electrical energy and the riding range.

- ✧ You should fully charge the battery before a long journey.
- ✧ Rough road conditions and hilly terrain will consume more energy.
- ✧ Frequent change of speed will consume more energy.
- ✧ Carrying more weight on the e-bike will consume more energy.
- ✧ Keeping the tires properly inflated and keeping the e-bike clean and well lubricated will save energy.
- ✧ Making sure that both wheels move freely when brakes are not applied will save energy. You should check brake adjustments frequently.
- ✧ Pedaling as you ride will consume less electrical energy and increase the riding range.
- ✧ When the battery is turned off, your e-bike functions as a regular bicycle. If you embark on a very long journey, you might want to turn off the battery for long stretches where the road is level or downhill and pedal the e-bike as a regular bicycle so that you can conserve electrical energy stored in the battery.

Care and Maintenance for Your New e-Bike

You should, in general, take care of your e-bike the way you would with a regular bicycle by keeping it dry, clean and the moving parts well lubricated. You should also avoid parking your e-bike in exposed areas whenever possible.

You should check the effectiveness of the brakes before each use.

● For your e-Bike, you should also take note of the following:

- ✧ Your e-bike is designed for regular country road use for a single person. Using your e-bike for extreme maneuvers, such as extreme off-road use, jumping, or carrying the excessive load will damage the e-bike and could cause serious injury.
- ✧ Do not use high-pressure water streams to clean your e-bike, as water might seep inside the motor or the wiring compartment and cause rusting of electrical parts or short circuits.
- ✧ Avoid parking your e-bike outside when there is rain or snow. At the end of a trip where there was rain or snow, bring the e-bike inside and use a clean, dry towel to eliminate any wetness.
- ✧ Be sure you do not lose both keys and remote controls. If you lost one key, you should immediately make a copy as a back-up. If you lost both keys, you will be unable to remove the battery from the e-bike. If you lost both remote controls, you can't turn on the bike.

● Special Care for the Battery and the Charger

- ✧ Use only the supplied charger to charge your battery. Do not use an unauthorized substitute. If your charger is lost or damaged, contact your dealer to order a replacement.
 - ✧ Do not open or alter the battery or the battery charger.
 - ✧ Do not place the battery near fire or corrosive substances. Do not immerse in water or other liquids.
 - ✧ Avoid subjecting the battery from high temperatures, such as directly under the hot sun, for prolonged periods of time.
 - ✧ Do not connect (short circuit) the two poles of the battery.
 - ✧ After much use, your battery's charge holding capacity will decrease. If you find that your battery does not hold sufficient charge even for short trips, you should contact your dealer to order a replacement. Under normal use, the battery will undergo 500 charging and discharging cycles.
 - ✧ If the battery will not be used for an extended period of time, charge it fully and recharge it every month. Store it in a cool place.
- ² Your e-bike battery is engineered with precision for high capacity and long useful life. We do not recommend that you use it to power other electrical devices. Improper use of the battery will damage the battery and shorten its useful life and may cause a fire or an explosion.

1. Production Name

Central Installed Negative LCD, model UKS2-Plus

2. Parameters


- ✧ 24V/36V/48V/60V/72V/UBE power supply
- ✧ Rated power 1W
- ✧ Max power: 5W
- ✧ USB charging parameter DC 5V 500mA
- ✧ Power off leak current < 1uA
- ✧ Working current supplied to controller: 50 mA
- ✧ Operating temperature -20~70°C
- ✧ Storage temperature -30~80°C

3. Product Appearance and Material

ABS product shell

LCD transparent window is made of reinforced glass film

Product holder material is glass fiber mixed with nylon.






4. Product Introduction



- ✧ **Speed indicator:** “RT SPEED”, “MAX SPEED”, “AVG SPEED”

- ❖ **Unit system:** Users can either change it to metric or imperial.
- ❖ **Intelligent battery indicator:** Provide stable battery reminder through optimization algorithm, power is not affected by motor start-stop fluctuations. If the system supports battery communication, it can display accurate percentage power
- ❖ **Backlight brightness:** It has an option from 1 to 5.
- ❖ **Assist level:** can be set as needed, like 3/5/9/6
- ❖ **Mileage indicator:** “ODO”, “Trip”, “Time”
- ❖ **Output power indicator:** It can display real-time output power of the battery
- ❖ Error code indicator.
- ❖ **Walk mode:** support 6km push assist
- ❖ **Speed measuring magnets number adjustment:** numbers can be set according to the actual requirements of customers
- ❖ **PAS magnets number adjustment:** numbers can be set according to the actual requirements of customers
- ❖ **Endurance mileage indication (requires battery to support communication)**
- ❖ **Battery indicator (requires battery to support communication)**
- ❖ **USB charging port: can provide rated charging for mobile devices, current: 500mA / 5V**
- ❖ Software can be upgraded by UART. For detailed information, please refer to related documents.
- ❖ **Parameter setting:** parameters can be set, including assist levels, wheel size, voltage, speed limit, limit current, etc. Please refer to the description of parameter setting operation steps.

6. Screen Instructions



- ✦ **Speed indicator:** AVG SPEED, MAX SPEED, RT SPEED
- ✦ **Speed mode:** It is displayed as Km/h or MPH
- ✦ **Power Indicator:** It provides stable battery reminder through optimization algorithm. Power is not affected by motor start-stop fluctuations. If the system supports battery communication, it can display accurate percentage power
- ✦ **Headlight indicator:** The icon  shows up on the screen when the headlights are on
- ✦ **Brake Indicator:** When the brake is power off, the icon  shows up on the screen.
- ✦ **Assist level:** It has an option from 0 to 9. 0 is for neutral. When the bike goes into 6km push assist mode, the screen displays P.

- ✧ When an error is detected, an icon  will be displayed on the screen.
- ✧ **Mileage mode:** “TRIP”, “ODO”, “TIME”.
- ✧ **Mileage display:** Displays mileage information or time information.
- ✧ The icon  means USB function has been enabled.

7. Function Description

Button description as follow:




7.1 Power On/Off

Press and hold POWER button to turn on or turn off the display. The display will automatically shut down when there is no operation& ride for 5 minutes (time can be set by users) .

***If the display has been set power-on password, you need to input the right password to launch.**


7.2 PAS Level

In the manual shift mode, short press PLUS or MINUS to switch the assist level and change the assist ratio. Top assist level is 9. The default value is 1st when the display is turned on, and 0 is the neutral assist.




7.3 Mileage Mode Switch

When power on, short-press POWER to switch the mileage display mode. And the following information is displayed cyclically: riding time (Time) → accumulated mileage (ODO) → power information (Pow) → single mileage (Trip) → outdoor temperature.



7.4 Speed Mode Switch

Press M button to switch the speed display mode, and the following information is displayed cyclically:
 real time speed (RT SPEED) → average speed (AVG SPEED) → maximum speed (MAX SPEED).



Real time speed(SPEED) /Trip


Max Speed (MAX)

Average Speed (AVG)

*If there is no key operation for 5 seconds, the system will automatically return to the real-time speed display state.

7.5 Headlight / Backlight Switch

Press and hold PLUS button to lower the backlight brightness. And the lights are turned on (requires controller support). Press and hold PLUS button again (1 second), the display backlight recovers, and the lights will be turned off at the same time.



Headlight off

Headlight on

* Backlight brightness can be adjusted in 5 levels. Users can set it as needed.

7.6 Walk Mode(6km push assist)

Press and hold MINUS button longer than 1 second to enter walk mode. And the screen shows P. When release the button, it will exit the mode.



Walk Mode Off



Walk Mode On

*Some controllers may not support this function

7.7 USB Function

Hold on M button longer than 1 second, USB charger is on. Hold on M button longer than 1 second again, USB charger is off. Charging parameters: DC 5V 500mA.



USB OFF



USB ON

7.8 Data Zero Out

To zero the data out, including AVG Speed, MAX Speed, Trip and Time, hold PLUS and MINUS buttons for a few seconds.

*These temporary data will not be erased when the display or the bike is powered off.


8. MENU Parameter Setting

Press the M button twice within 0.3S, it will enter the menu. Press M button twice again to exit (time interval must be within 0.3S).


Press M Button to select the desired adjustment item and the item starts flashing. Click PLUS button and MINUS button to adjust the parameters. Press POWER button to save and switch item. Double tap M to exit the menu.

*In the parameter setting state, if no key operation is performed for 30 seconds, the system will automatically exit. In the riding state (the speed indication is not 0), it cannot enter the setting interface. If you start cycling in the setting interface (the speed indicator is not 0), it will automatically exit the setting.

8.1 The display setting items are as follows:




- ✧ **P1: Backlight Brightness:** Press PLUS and MINUS button to select brightness levels. It has five options from 1 to 5.




Backlight Brightness Adjust Interface

- ✧ **P2: Auto power off time:** Press PLUS or MINUS button to adjust auto off time. 1 ~ 9 minutes represents the automatic shutdown time. Or you can click OFF to cancel the auto off function.




Automatic Shutdown time Adjust Interface

- ✧ **P3: Universal/ Imperial:** Press PLUS and MINUS button to switch km / h or MPH. 0 stands for universal system and 1 stands for imperial system.




Universal/ imperial Switch Interface

- ✧ **P4: Manual / Automatic Switching:** Press PLUS or MINUS button to select manual / automatic switching. 0 means manual, 1 means automatic.




Manual / Automatic Switch Interface

- ✧ **ADS: Password input:** Press PLUS or MINUS button to set the password value (0 ~ 9) and press M button to switch the password item. The default password "1801". Press M Button to confirm. If the password is wrong, "Error" will be displayed, and the display will automatically return to the real-time speed /single mileage display state. If the password is correct, enter the advanced settings sub-item.




Password Input Surface


- ✧ **Factory restore setting:** Press M button to enter the interface and select RES to restore to factory setting. All the data will be restored to factory setting except ODO. Select OFF or long press POWER ti return to main menu.



8.2 The advanced setting items are as follows:




- ✦ **A1: Voltage:** Press PLUS or MINUS to switch between 24V / 36V / 48V / 60V / 72V / UBE. UBE stands for user-defined voltage (the voltage value can be set by a computer program. For details, please refer to the computer parameter setting instruction file).




Voltage

- A2: Assist level selection:** Press PLUS or MINUS button to set the assist level 3/5/9/6.




Assist level selection Interface

- ✧ **A3: Speed Limit Adjustment:** Press PLUS or MINUS button to adjust the speed limit value. The default value is 25km / h. Users can set the speed limit value as needed. Press POWER button to confirm and exit.



Speed Limiting Adjustment Interface


- ✧ **Current Limit Adjustment:** item A4, Press PLUS and MINUS button to adjust the current limit value. The default value is 15A. Users can set the current limit value according to their needs. Press POWER button to confirm and exit.



Current Limit Adjusting Interface


*Speed and current are restricted by the motor and controller at the same time and may not be able to reach the set value.

- ✧ **A5: Wheel Diameter/size Selection:** Press PLUS or MINUS button to switch the wheel size 16/18/20/22/24/26/27 / 700C / 28/29/30/31/32. Select the corresponding wheel diameter and the unit is inch. Incorrect selection of wheel diameter will lead to abnormal speed.




Wheel Diameter Selection Interface

- ✧ **A6: Number of speed measuring magnets:** Press PLUS or MINUS button to adjust the number of speed measuring magnets from 1 to 72. The user can set the number of speed measuring magnets as needed. Then press POWER button to confirm and exit.(It cannot be adjusted as user's requirement)




Number of speed measuring magnets Selection Interface

- ✧ **A7: Number of PAS magnets:** Press PLUS or MINUS button to boost the number of booster magnets 3 ~ 15. The user can set the number of PAS magnets as needed. Then press POWER button to confirm and exit.




Number of PAS magnets Selection Interface

- ✧ **A8: Throttle 6km.** Press UP/DOWN to modify the mode. Users can change it from 0 to 3. 0 means throttle 6Km off and 1 means it is on. Under the two modes, even you turn the handlebar, there is no gear difference. Switch to 2, throttle 6Km is off. Switch to 3, throttle 6Km is on. Under the two modes, when you turn the handlebar, there is gear difference.




Throttle 6KM Adjust Interface

- ✧ **A9: PAS orientation:** Press PLUS or MINUS button to select the direction of the power sensor.




PAS orientation Adjustment Interface

- ✧ **A10: Cruise control:** Press PLUS/MINUS to turn on or off. 0: ON. 1: OFF



9. Error Code Definition


UKS2 can provide error indications for vehicle faults. When a fault is detected, the LCD screen displays , and the error code “n” and error description are displayed at the speed display position. Please refer to the error code comparison table to determine the corresponding fault.



Error Warning Interface

10. Installation Instruction

10.1 Please refer to the following figure for the instrument screw assembly. Pay attention to the screw tightening torque. Instrument damage caused by excessive torque is not covered by the warranty.



Screw Installation Drawing


10.2 Clips are suitable for three handlebar sizes, 31.8mm, 25.4mm, and 22.2mm. Customers can choose according to actual needs.

And 25.4mm and 22.2mm need to be matched with corresponding conversion.



11. Cable Outlet Definition

The color of the five-core waterproof line is <red, blue, black, green, and yellow>. The order is defined as follows:



- 1、 RED: Power+ (Battery power 24V/36V/48V)
- 2、 Blue: Controller lock cable
- 3、 Black: GND
- 4、 Green: RXD display input signal, display receives signal from controller
- 5、 Yellow: TXD display output signal, display sends signal to controller

Safety

These safety precautions are provided for your benefit to protect you and those around you. Please read and follow them carefully to avoid unnecessary injury, damage to the product, or damage to other property.


Battery

⚠ CAUTION

- Do not throw the battery into a fire. Do not overheat the battery.



- Do not connect the battery to other appliances other than your battery.




- Use only the specified charger to charge the battery.



- Do not take apart or modify the battery.



- Do not connect positive and negative terminals by using metallic objects.



(Elcclrolyle leakage, overheating and/or rapture may result in this type of abuse.)

Battery Charger

⚠ CAUTION


- Do not take apart or modify the charger



- Do not subject the charger to shocks, e.g. by dropping. Keep the charger away from water




- Do not touch the charger with your skin for long periods during charging




Overheating, fire or electric shock may result


- Do not cover the charger or place objects on it



- Place the charger firmly on a flat dry surface



- Do not short-circuit the terminals by using metallic objects



⚠ WARNING

- Keep the battery away from water. Pouring water on the battery may result in short-circuit, overheating or permanent damage of the battery.
- Do not submerge the battery. Soaking the battery in water may cause irreparable damage.

⚠ WARNING

- Do not apply pressure to the cable or the plug.
 - ⊘ Placing the cable tightened between a wall and a window frame, or placing heavy objects on the cord or the plug may result in electric shock or fire.
- Be sure to insert the plug securely into a wall socket.
 - ⊘ Electric shock and overheating may result, causing fire.
- Do not touch the plug with wet hands.
 - ⊘ Electric shock may result.
- Keep out of reach of children or pets.
 - ⊘ Electric shock or injury may result.
- Do not attempt to use another maker or model's charger to charge the battery.
 - ⊘ Overheating, fire or electric shock may result.
- Do not use the charging plug and/or the power source Plug when they are dirty, wet or dusty.
 - ⊘ Insulation failure due to moisture absorbed in the dust may result, causing fire.
 - Pull out the power source plug and clean it with a dry cloth.
- To remove a cable from a socket, pull the plug, not the cable.
 - ⊘ Always pull the charging cable gently.
- Do not rotate the pedals when charging the battery while it is mounted on the bicycle.
 - ⊘ The cord may twist around the pedal or the crank, and the damage to the plug may result, causing electric shock or fire.
- Do not apply voltage over the rated value to the charger.
 - ⊘ Do not use sockets, correctors and other wiring devices with a power source other than standard rated voltage (AC110-240 volts) power supply.
 - Overheating, fire or electric shock may result.
- Do not use damaged components such as charge case, power cord, plug etc.
 - ⊘ Electric short, short-circuit or fire may result.

Trouble Shooting

As one or more causes of failure might lead to the failure phenomenon, you should find out the true cause(s) and then take the appropriate solution(s) to rectify the problem. In case of doubt, please consult a qualified technician for service, repairs or maintenance.

Failure Phenomena	Causes of Failure	Solutions
<ul style="list-style-type: none"> • Can't turn on the e-bike 	<ul style="list-style-type: none"> • Battery is off • The Battery is out of power • Battery aging or damaged • Poor contact of display line • Failure of controller • Failure of switch 	<ul style="list-style-type: none"> • Turn on the battery • Fully charge the battery • Replace the battery • Reconnect the display • Replace the controller • Replace the switch
<ul style="list-style-type: none"> • Pedal assist doesn't work • Gear doesn't work well • Brake doesn't work well • Display doesn't light on 	<ul style="list-style-type: none"> • Failure of speed sensor • Rear derailleur mismatch • Brake caliper mismatch • Brake Disc is bent • Poor contact of display line 	<ul style="list-style-type: none"> • replace speed sensor • Adjust rear derailleur • Adjust brake caliper or disc • Reconnect the display line
<ul style="list-style-type: none"> • Can't adjust the speed • Speed is less than 10km/h 	<ul style="list-style-type: none"> • Battery's voltage is too low • Throttle governing bar is damaged • Poor contact of the controlling line • Spring failure or being locked 	<ul style="list-style-type: none"> • Fully charge the battery • Replace the throttle governing bar • Replace the spring
<ul style="list-style-type: none"> • e-Bike's mileage is obviously inadequate after fully charged 	<ul style="list-style-type: none"> • Inadequate tire pressure • Failure of charger • The battery cannot be fully charged • Failure of controller • Battery aging or battery damaged • e-Bike has not been well assembled • Too much upgrade road • Strong wind • Bad road • Overweight • Too many braking times • Temperature is too low 	<ul style="list-style-type: none"> • Inflate tire with appropriate air pressure • Repair the charger • Examine and repair the controller • Replace the controller • Replace the battery • Re-adjust the e-Bike <ul style="list-style-type: none"> • Boost the e-Bike by manpower • Warm the battery above 0°C (32°F)
<ul style="list-style-type: none"> • Wheel hub stop running after switching on the power 	<ul style="list-style-type: none"> • The connection of battery is loosen. • Poor contact of controlling line • The connection of wheel hub is loose or damaged • The protective board of the battery is broken 	<ul style="list-style-type: none"> • Re-connect the battery • Replace the connection line • Replace the battery's protective board with a new one



Company: Guangzhou Weitianlan E-commerce Trade Co., Ltd.
Address: Room 202, No.4, Ivgang Fifth Street, Huadu District,
Guangzhou, Guangdong, China

Email: support@vitilanebike.com

Website: vitilanebike.com

Facebook: Vitilanebike

Youtube: Vitilanebike

Instagram: Vitilanebike

Twitter: Vitilanebike