

# Compare our portable power packs



|                                 | Batt Pack Energy                                                                    | Batt Pack Pro                                                                                                 | Batt Pack Jupiter                                                     |
|---------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| <b>AC Inverter</b>              | 3,000W                                                                              | 5,000W                                                                                                        | 7,000W                                                                |
| <b>Surge Power</b>              | 4,500W (500ms)<br>6,000W (10ms)                                                     | 7,000W (500ms)<br>10,000W (10ms)                                                                              | 12,000W (1sec)                                                        |
| <b>Loaded Motor Capacity</b>    | +2HP                                                                                | +3HP                                                                                                          | +5HP                                                                  |
| <b>Energy</b>                   | 2.5kWh                                                                              | 5.1kWh                                                                                                        | 7.2kWh                                                                |
| <b>Chemistry</b>                | LiFePO4                                                                             |                                                                                                               |                                                                       |
| <b>Cycles</b>                   | +3,500 Cycles                                                                       |                                                                                                               | +3,000 Cycles                                                         |
| <b>Voltage</b>                  | 120V AC*                                                                            |                                                                                                               | 120V AC and 240V AC                                                   |
| <b>Frequency</b>                | 60 Hz                                                                               |                                                                                                               | 50 Hz / 60 Hz                                                         |
| <b>Solar Input Power</b>        | 1,600W                                                                              | 5,500W                                                                                                        | 800W                                                                  |
| <b>Solar Input Voltage</b>      | 30-80V DC                                                                           | 125-450V DC                                                                                                   | 29-75V DC                                                             |
| <b>Max Solar Amperage</b>       | 40A                                                                                 |                                                                                                               | 30A                                                                   |
| <b>Grid Charging Power</b>      | 1,200W                                                                              |                                                                                                               | 1,110W                                                                |
| <b>Bypass Power</b>             | 1,200W                                                                              |                                                                                                               | N/A                                                                   |
| <b>Sine Wave</b>                | Pure Sine Wave                                                                      |                                                                                                               |                                                                       |
| <b>Output Voltage Threshold</b> | 5%                                                                                  |                                                                                                               |                                                                       |
| <b>Dimensions</b>               | 50.2cm x 40.8cm x 25.6cm<br>[19.8in x 16.1in x 10.1in]                              | 64.7cm x 50.8cm x 30cm<br>[25.5in x 20in x 11.8in]                                                            | 91.4cm x 68.5cm x 58.4cm<br>[36in x 27in x 23in]                      |
| <b>Weight</b>                   | 38 kg [83.7 lbs]                                                                    | 63.5 kg [140 lbs]                                                                                             | 127 kg [280 lbs]                                                      |
| <b>Storage Temperature</b>      | -30°C to 50°C [-22°F to 122°F]                                                      |                                                                                                               | -20°C to 45°C [-4°F to 113°F]                                         |
| <b>Operating Temperature</b>    | -30°C to 50°C [-22°F to 122°F]                                                      |                                                                                                               | -20°C to 45°C [-4°F to 113°F]                                         |
| <b>Certification</b>            | UL9540A, UL1642, CSA SP-1000, ULI741                                                |                                                                                                               | CSA SP-1000, UL-458                                                   |
| <b>Safety Features</b>          | <ul style="list-style-type: none"> <li>Solar reverse polarity protection</li> </ul> | <ul style="list-style-type: none"> <li>Short circuit protection</li> <li>Over temperature shut off</li> </ul> | <ul style="list-style-type: none"> <li>Overload protection</li> </ul> |

\* 240V AC 50 Hz model available upon request, subject to MOQs  
 \*\*Custom colours available, subject to MOQs.



**ATTENTION:** Please note it is the customer's obligation to check local electrical requirements and certification requirements of all HPS purchased equipment to ensure they meet the local electrical code. Additional components such as AFCI protection, Conduit Caps, and fusing/breakers may be required.