COMET 1 FLOOD SMD 10w



age- 10w Age 240v AC ur Temperature (k)- 5000K m Angle- 80° en output- Globe Dependant p Base- LED integrated SMD 84+ Ating- 1P44 hable No surface Surface			
age240v ACur Temperature (k)-5000Km Angle-80°en output-Globe Dependantp Base-LED integrated SMD84+84+ating-IP44mableNonting Type-Surface	Product Code-	IFL-COMET-EX1-BK	
ur Temperature (k)- M Angle- en output- p Base- LED integrated SMD 84+ Ating- Mable No Surface Surface	Vattage-	10w	
m Angle- en output- p Base- tet ing- tet ing- mable nting Type- Matrice Surface Base- No Surface Base- Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Sufface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Surface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface Sufface	/oltage	240v AC	
en output- p Base- tating- mable nting Type- Base- LED integrated SMD 84+ IP44 No Surface Integrated SMD 84+ Integrated SMD 11.2	Colour Temperature (k)-	5000K	
p Base-LED integrated SMD84+ating-IP44mableNonting Type-Surface	Beam Angle-	80°	
p Base-LED integrated SMD84+ating-IP44mableNonting Type-Surface	umen output-	Globe Dependant	25
84+ating-IP44mableNonting Type-Surface	amp Base-	LED integrated SMD	
mable No Virface	RI-	84+	$ \nabla \rangle$
nting Type- Surface	o Rating-	IP44	
	Dimmable	No	\bigvee
Polycarbonate	lounting Type-	Surface	
	laterial-	Polycarbonate	
ur- Black	Colour-	Black	
anty- 3 Years Replacement	Varranty-	3 Years Replacement	



20