KOBE TRACK LIGHT



This track light is available in three meticulously selected finishes – black with black trim, black with gold trim and white with black trim.

Kobe 8W Track Light

Finish

UV Textured Black Black / Gold Trim White / Black Trim

Power

8 Watts

Lumen Output

720 Lumens at 3000K 765 Lumens at 4000K

Measurements

Diameter: 74mm Depth: 135mm

Beam Angles

15° | 36° | 60°

Colour Temperature

3.000K ☐ 4 000K

IP20

CRI 92+

Colour Deviation SDCM ≤ 3

(MacAdam)

Lifetime Reported

L70 > 36,000h Calculated L70 - 123,000h

-Kobe 15W Track Light

UGR < 13

Power Factor > 0.90

Driver 240V Built-in Driver

Dimming LED Phase-Cut

Dimmer, Trailing Edge

Track Mount

Single and three circuit track adaptor available

Finish

UV Textured Black Black / Gold Trim White / Black Trim

Power

15 Watts

Lumen Output

850 Lumens at 3000K 1050 Lumens at 4000K

Measurements

Diameter: 74mm Depth: 160mm

Beam Angles 15° | 36° | 60°

Colour Temperature

□ 3 000K

☐ 4,000K

IP20 CRI 92+

Colour Deviation

SDCM ≤ 3 (MacAdam)

Lifetime

Reported L70 > 36,000h Calculated L70 - 123,000h

UGR < 13

Power Factor > 0.90

Driver

240V Built-in Driver

Dimming

LED Phase-Cut Dimmer, Trailing Edge

Track Mount

Single and three circuit track adaptor available

Kobe 26W Track Light

Finish

UV Textured Black Black / Gold Trim White / Black Trim

Power 26 Watts

Lumen Output 1875 Lumens at 3000K 2075 Lumens

at 4000K Measurements

Diameter: 102mm Depth; 168mm

Beam Angles 15° | 36° | 60°

Colour Temperature

3,000 ☐ 4,000K

IP20

CRI

Colour Deviation SDCM ≤ 3 (MacAdam)

Lifetime Reported L70 > 36,000h

L70 - 123,000h

Calculated

UGR < 13

Power Factor > 0.90

240V Built-in Driver

Dimming LED Phase-Cut Dimmer. Trailing Edge

Track Mount

Single and three circuit track adaptor available

Kobe 35W Track Light

UV Textured Black Black / Gold Trim White / Black Trim

Power

35 Watts

Lumen Output 2365 Lumens

at 3000K 2800 Lumens at 4000K

Measurements

Diameter: 102mm Depth: 188mm

Beam Angles 15° | 36° | 60°

Colour Temperature

☐ 4,000K **IP20**

CRI 92+

Colour Deviation (MacAdam)

Lifetime

Reported L70 > 36,000h Calculated L70 - 123,000h

UGR < 13

Power Factor > 0.90

Driver

240V Built-in Driver

Dimming

LED Phase-Cut Dimmer, Trailing Edge

Track Mount

Single and three circuit track adaptor available