

## Handling and Lifting GT Permanent Magnetic Lifter

The Handling and Lifting GT Permanent Magnetic Lifter lends itself to easy operation and handling.

### Product Specifications

- Permanent Magnetic Lifter for safe, easy operation and handling.
- Designed for the lifting & handling of magnetic material.
- Requires no extra power, strong magnetic force.
- Red painted finish.
- Conforms to BS EN 13155.
- Temperature range -40°C up to +80°C.
- Marked in accordance with BS EN 13155.
- Certification available



| Product Code | Plate Capacity | Cylindrical Capacity | Tear-Off Force | H   | I   | L   | W   | Weight |
|--------------|----------------|----------------------|----------------|-----|-----|-----|-----|--------|
|              | kgs            | kgs                  | kgs            | mm  | mm  | mm  | mm  | kgs    |
| PML100       | 100            | 30                   | 350            | 70  | 142 | 92  | 64  | 3      |
| PML300       | 300            | 100                  | 1,050          | 96  | 176 | 165 | 88  | 10     |
| PML600       | 600            | 200                  | 2,100          | 120 | 219 | 236 | 118 | 24     |
| PML1000      | 1,000          | 300                  | 3,500          | 168 | 266 | 264 | 168 | 50     |
| PML2000      | 2,000          | 600                  | 7,000          | 217 | 462 | 378 | 230 | 125    |
| PML3000      | 3,000          | 1,000                | 10,500         | 265 | 567 | 453 | 290 | 220    |
| PML5000      | 5,000          | 1,500                | 17,500         | 265 | 707 | 647 | 290 | 355    |
| PML6000      | 6,000          | 2,000                | 19,200         | 265 | 707 | 713 | 290 | 398    |