

EASY INSTALLATION

Two Power settings: 12W & 25W 3K, 4K Switch

Removable Terminal Block

erminal Block

the terminal and twist locks onto the base.

Convenient Twist on Mounting Plate

Easy plug connection

LUMINAIRE SPECIFICATION:

Model	ACL12-25W2T
Impact resistance	.IK10
Dimmable	.10% - 100%
Beam Angle	.120 degrees
Lumens	1200Lm/2500Lm
Wattage	.12W/25W
IP Rating	IP65
Colour temperature	.Switchable 3000K/4000K
Input Voltage	.220-240 Volts ~ 50/60Hz
Mounting Type	.Surface Mounted

DUAL LUMENS

This light has been designed for quick and simple installation. The fitting comes with a full

base plate for separate ease of fixing. The centrally located cable entry, along with easy clip in terminal block, makes for convenient termination. The light then simply plugs into

This light comes with an easily accessible switch so it can be either 1200 lumens (12W) or 2500 lumens (25W)

2 COLOR TEMPERATURES

This light comes with an easily accessible switch so it can be either 3000k or 4000k.

OPTIONAL CONDUIT BASE MOUNT

This Conduit base is compatible with all the models in this range. The IP65 base comes complete with both 20mm & 25mm 'pre-threaded' entry points for conduit.

