



PRODUCT FEATURES

Linemarker paint is an acrylic-based aerosol paint suitable for marking car parks, factory floors, stores and warehouses. In conjunction with a range of precision engineered, easy to use applicators, it produces bright, sharp and durable lines.

KIT FORM

750ml Aerosol

COVERAGE

Approximately 100m of a 55mm wide line. Coverage figures will vary according to the texture, porosity and evenness of the surface on which the Linemarker is being applied.

STORAGE

Store at temperatures between 5°C and 30°C

SHELF LIFE

Approximately 48 months if stored in good conditions.

SURFACE PREPARATION

The surface must be clean, dry and free from dust, laitance oils, paints or other forms of contamination.

MIXING

It is important to mix the contents of the can sufficiently before use. This is done by shaking the can until you can hear the agitator ball and then continue shaking for 30 seconds.

APPLICATION

Once mixing is complete the Linemarker can be applied via freehand or by use of a wheel applicator.

CLEANING

Once mixing and application are complete; tools can be cleaned with acetone.

CURING TIME

Depending on temperature the Linemarker paint will be touch dry in 15 to 30 minutes and should be allowed to cure for 24 hours.

OVERCOATING

Subsequent coats of Linemarker paint should be applied no later than 24 hours after the first coat has cured.

WORKING CONDITIONS

Linemarker paint should not be applied at temperatures below 10°C

HEALTH AND SAFETY

Consult the Material Safety Data Sheet prior to use.

GENERAL GUIDANCE

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.