## #2745 - Stretch Belt Installation Tool - Small #2747 - Stretch Belt Installation Tool - Large

- · Quickly and easily install stretch belts found on many late model vehicles
- These drive systems do not have a tensioner and require the proper installation tools to avoid damage
- #2745 Applications: Ford, Lincoln, Mercury, Mazda, Chevy, GMC, Hummer, Cadillac, Isuzu, Chrysler, Dodge
- #2747 Applications: BMW, Volvo, Mercedes, Mazda
- MADE IN USA



CAUTION: To prevent injury, always wear gloves and eye protection that meets ANSI Z87.1 and OSHA standards. CAUTION: To prevent equipment damage, clean and lubricate threaded screws and holes before and after use.

## **INSTRUCTIONS:**

- 1. Locate the stretch belt on the vehicle that needs to be installed or replaced. Refer to the vehicle's service manual for details on accessing the belt.
- 2. Thread the stretch belt through the installation tool, centering it between the tips. Ensure the belt is not twisted.
- 3. Position the installation tool and belt around the pulleys, aligning the belt with the pulley grooves.
- 4. Turn the installation tool clockwise while holding the tool firmly in position. This will stretch the belt and allow it to be installed around the pulleys.
- 5. Continue turning the handle until the belt is fully stretched and seated properly in the pulley grooves.
- 6. Remove the installation tool. The tension from the stretched belt will hold it in place around the pulleys.
- 7. Spin the pulleys several times by hand to ensure proper alignment and operation.
- 8. Refer to the vehicle service manual and reset or recalibrate any sensors or systems as required after belt replacement.
- 9. Confirm proper belt operation by starting the vehicle and testing all functions related to the belt system.







