

CABPRO 2610 PVC ELECTRICAL TAPE PROFESSIONAL GRADE

The CABPRO 2610 is a 0.15mm professional grade, weather resistant, pressure sensitive vinyl tape for all kinds of mechanical and electrical applications. CABPRO 2610 is flame retardant and can be used as primary insulation for splices up to 600 volts. VDE Lead-free.

Recommended uses:

Used for general splicing purposes. Can be used as primary insulation for splices up to 600 volts and provides a protective outer jacket for splices at higher voltages. Can be used for wrapping wire harnesses and insulating degaussing coils. Colours can be used for colour coding electrical circuits.

FEATURES:

- 0.15mm thickness
- Flame retardant
- Meet RoHS & REACH
- Resistant to sun, water, oil, acids, alkalis, corrosive chemicals

SPECIFICATIONS

PROPERTY	TYPICAL VALUE	UNIT*	TEST METHOD
PHYSICAL			
Thickness	0,006	inch	IEC 60454-2
	0.15	mm	
Tensile Strength	16	lb/in	IEC 60454-2
	28	N/cm	
Elongation	200	%	IEC 60454-2
Adhesion To Steel	20	oz/in	IEC 60454-2
	2.2	N/cm	
Adhesion To Backing	18	oz/in	IEC 60454-2
	2.0	N/cm	
Flammability	Pass	-	IEC 60454-2
Temp. Rating	0~90	°C	IEC 60454-3-1
DIELECTRIC STRENGTH			
Standard	45	kv/mm	IEC 60454-2
Wet	40	kv/mm	IEC 60454-2

*Units N/cm describes Newtons per cm length of 19mm wide tape.

ORDERING INFORMATION:

PART NO.	DESCRIPTION	COLOUR	DIMENSIONS (W x L x T)
T030030BK	CABPRO PVC TAPE 2610	BLACK	19mm x 20m x 0.15mm
T030031BL	CABPRO PVC TAPE 2610	BLUE	19mm x 20m x 0.15mm
T030033RD	CABPRO PVC TAPE 2610	RED	19mm x 20m x 0.15mm
T030034WH	CABPRO PVC TAPE 2610	WHITE	19mm x 20m x 0.15mm
T030036RBW	CABPRO PVC TAPE 2610	RAINBOW 10PACK	19mm x 20m x 0.15mm
T030041YG	CABPRO PVC TAPE 2610	YELLOW/GREEN	19mm x 20m x 0.15mm
T030058GY	CABPRO PVC TAPE 2610	GREY	19mm x 20m x 0.15mm



In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.