

## 1045 series surface mount contacts

industrial magnetic contacts with wire leads

The 1045 series features a wider make distance, which permits faster installation, accommodates greater misalignment, and works better on steel without time-consuming brackets.

The wider distance also helps prevent false alarms caused by loose-fitting doors.



### Specifications

Voltage:	1045: 100 VAC/VDC max. 1047: 30 VAC/VDC max.
Current:	1045: 0.5 A max. 1047: 0.25 A max.
Power:	1045: 7.5 W max. 1047: 3.0 W max.
Loop type:	1045: Closed 1047: Open or Closed
Electrical configuration:	1045: Normally open 1047: SPDT
Gap distance:	Up to 3 in.
Lead type:	3 ft. vinyl jacketed
Dimensions (WxHxD):	3.9 x 0.7 x 0.6 in. (100 x 18 x 15 mm)
Housing:	Flame retardant ABS plastic
Color:	White, gray

### Ordering information

1045WN-5PKG	Industrial surface mount magnetic contact with wire leads, wide gap, 3 in. gap size, closed loop, white, pk/5
1045WG-5PKG	Industrial surface mount magnetic contact with wire leads, wide gap, 3 in. gap size, closed loop, gray, pk/5
1047H-N	Industrial surface mount magnetic contact with wire leads, 3/8 to 1-1/4 in. gap size, higher security applications, SPDT, white

- Rugged design ideal for metal entry/exit doors, overhead doors, roof hatches, hinged skylights, and other industrial applications
- Convenient surface mounting
- Mounting screws included
- Available wider gap distance helps prevent false alarms caused by loose-fitting doors and windows

