



Service Bulletin #303

SB-303
(012106)
ECR 9816

PLEASE READ CAREFULLY BEFORE PROCEEDING

KITS 74000/74000EZ (REQUIRED TO INSTALL PINK IGNITION WIRE FOR PROPER OPERATION)

Thank you for purchasing this product. Due to electronic component shortages which continue to impact businesses, there has been a change to this kit from the original design. This is a temporary change that does not affect the quality or function of the system. The original system configuration will return soon.

The motion-based “wake up” feature of the manifold has been removed. The system will only become active upon connection with a Bluetooth device (controller/smart phone) or when ignition is turned on. Therefore, connecting the pink wire to an ignition source is now required, varying from the details on page 5 of your manual, which states this as an option. A proper ignition source will have a constant 12V when the key is turned on.

Please see the table below for changes to your kit from the details noted in your installation guide. Note that there are no visible changes to the WirelessAir manifold. The necessary hardware to ensure proper operation has been provided.

MANUAL HARDWARE LIST

A	72710	WIRELESSAIR MANIFOLD	1
---	-------	----------------------	---

PROVIDED HARDWARE LIST

A	72713	WIRELESSAIR MANIFOLD	1
B	24503	FUSE 3A ATM	1
C	24501	FUSE HOLDER ATM	1
D	24661	BUTT SPLICE (14-16GA)	1
E	24524	TERMINAL SPADE .187"	1
F	24594	TERMINAL SPADE .250"	1
G	24561	ADAPTER ATM FUSE	1
H	24542	ADAPTER ATC FUSE	1

See the wiring integration instructions below for connecting to an ignition circuit found in most fuse boxes.

If your kit came with this Service Bulletin (SB-303) or your manifold is part number 72713, **you will be required** to follow the installation instructions noted in SB-303.

If your kit **did not** come with SB-303 and your manifold is part number 72710, please proceed with the normal installation, as outlined in your installation guide (MN-1092 or MN-1100).

