Solitaire | FANDELIGHT

61013

- Includes One 8" Downrod
- Includes Remote Control
- Title 20
- Color Tunable
- Wifi Enabled

Job Name : Job Type Quantity Comments:





PRODUCT DESCRIPTION

This romantic Fandelight delivers luxury appeal and timeless sophistication. Gracefully curved arms support a crown affixed with Beveled Crystals jewels. LED candelabra bulbs are positioned behind the crystal to illuminate each crystal individually. A Wi-Fi enabled control is housed in the canopy that can be either operated by the remote provided or Smart Home apps without the use of a bridge.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs





MEASUREMENTS	
DIMENSION	: 31" D x 20" H
MAX OAH	: 20" OAH
CANOPY	: 6.75" W x 2.75" H x 6.75" L
HANGING WEIGHT	: 20.06 lb
WIRE LENGTH	: 8"

LAMPING

INPUT VOLTAGE : 120V LUMENS : 2,000 Rated (1,800 Del.) BULB : 6 x 4W E12 LED , 24W Total DIMMABLE CRI

: By Control Provided : 80 CRI COLOR_TEMP : 3000K

ENERGY INFORMATION AT HIGH SPEED

AIRFLOW : 2440 CFM :20W ELECTRICITY USE AIRFLOW EFFICIENCY : 122 CFM / W



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com



ACCESSORIES (Sold Separately)



FCT6000WT Wall Control

FINISHES OPTION



MATERIAL Glass+Steel+ABS

RATINGS

cETLus Damp Location

INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118SM)
- 24" (FRD0124SM)
- 30" (FRD0130SM) 36" (FRD0136SM)



ADDITIONAL

RATED LIFE: 20,000 Hours **OPERATING TEMPERATURE: -20°** C (-4°F), 40°C (104°F) LIGHTING DIRECTION: Down