

Bancroft® Single-function Showerhead K-14519-G

Features

- Single-function showerhead with 48 nozzle 5-15/16" (151 mm) diameter sprayface.
- Optimized sprayface for maximum performance.
- MasterClean[™] sprayface features an easy-to-clean surface that withstands mineral buildup.
- Complements Bancroft faucets and accessories.
- 1.75 gpm (6.6 lpm) maximum flow rate.

Technology

 Katalyst® air-induction technology infuses water with air, creating bigger drops for a more powerful spray.

Installation

1/2" (12 mm) 14 NPT connection.

Recommended Products/Accessories

K-7397 Shower Arm and Flange K-23723 Faucet cleaner





Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC)

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes


Color tiles intended for reference only.


Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	BN	Vibrant® Brushed Nickel
	2BZ	Oil-Rubbed Bronze





Bancroft® Single-function Showerhead K-14519-G





Technical Information

All product dimensions are nominal.

Showerhead/Body Spray:

Rated maximum 1.75 gal/min (6.6 l/min)

flow:

Pressure: 80 psi (5.5 bar)

Notes

For use with automatic compensating valves rated at 1.4 gal/min (5.3 l/min) or less. Install this product according to the installation instructions.

