

# Loure® Rite-Temp® Diverter Shower Valve Trim K-T14665-4

### Features

- Includes valve trim with handle, bath spout, shower arm and flange, and showerhead.
- Single handle controls both on/off activation and temperature settings.
- Integrated push-button diverter.
- Optimal water coverage provided by large showerhead diameter.
- MasterClean<sup>™</sup> sprayface features an easy-to-clean surface that withstands mineral buildup.
- High-temperature limit stop allows you to preset a comfortable maximum temperature to eliminate scalding.
- Coordinates with Loure faucets, accessories, and showering components to complete your bathroom.
- Pressure-balancing diaphragm technology maintains outlet temperature within +/-3°F during water pressure fluctuations.

#### Material

- Premium material construction with metal handle ensures reliability and durability.
- KOHLER finishes resist corrosion and tarnishing.

## Installation

- Trim only; requires valve to complete installation (sold separately).
- Ease of installation with slip-fit connection.

#### **Required Products/Accessories**

K-11748-K Pressure-Balancing Valve w/Diverter or

K-11748-KS Pressure-Balancing Valve w/Diverter

#### **Recommended Products/Accessories**

K-23723 Faucet cleaner

#### **Optional Products/Accessories**

1139260 Deep Rough-In Kit





## **Codes/Standards**

ASME A112.18.1/CSA B125.1

#### **KOHLER®** Faucet Lifetime Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chr
	SN	Vibrant® Poli

CP Polished Chrome

- SN Vibrant® Polished Nickel
- Vibrant® Brushed Nickel BN



# KOHLER. Faucets

# Loure® Rite-Temp® Diverter Shower Valve Trim K-T14665-4



#### **Technical Information**

All product dimensions are nominal. Drain included: No

#### Showerhead/Body Spray:

Rated maximum 2.5 gal/min (9.5 l/min) flow:

#### Notes

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install a shut-off device on either valve outlet.

